

JUN 03 1983 6-3-1983

CONSERVATION DIVISION
Wichita, Kansas

To:
STATE CORPORATION COMMISSION
CONSERVATION DIVISION - PLUGGING SECTION
200 COLORADO DERBY BUILDING
WICHITA, KANSAS 67202

API NUMBER 15- 54

SW, Sec. 36, T 20 S, R 12 W 8
1650 feet from MS section line

990 feet from W section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5238

Lease Name Dannsbahn Well # 10

Operator: Petroleum Inc.
Name &
Address 368 W. Douglas, Wichita, Ks.
67202

County Barton

Well Total Depth 3435 feet \$111.64

Conductor Pipe: Size feet

Surface Casing: Size 8 5/8" feet 260

Abandoned Oil Well ☒ Gas Well ☐ Input Well ☐ SWD Well ☐ D&A ☐

Other well as hereinafter indicated

Plugging Contractor Rockhold Engineering, Inc. License Number 5111

Address Box 698, Great Bend, Ks. 67530

Company to plug at: Hour: Day: 1 Month: 6 Year: 1983

VERBAL PLUGGING ORDERS GIVEN TO D. B. Parlie

(company name) Rockhold Engineering, Inc. (phone) 316-793-6686

were: Order 165 lbs. 50 pps mix - 4 1/2" lead - 3% cal. U., 5 lbs. bulls,
15 lbs. Gels, to 8 5/8" plug.

Signed [Signature]
(TECHNICIAN)

Plugging Operations attended by Agent?: All ☒ Part ☐ None ☐

Operations Completed: Hour: 12:00 Noon Day: 1 Month: 6 Year: 1983

ACTUAL PLUGGING REPORT 8 5/8" - 260' SP. case w/ 200 lbs. 5 1/2" set at 3435'
Plugged back to 3420'. Top perf. at 3377'. Plugged bottom
w/ 5 lbs. cement, sand & 5 lbs. cement to 3375'. Shot pipe
1 time & recovered 300' after, ported. Pumped in 8 5/8", 4 lbs. bulls,
12 lbs. Gal., 65 lbs. cement, 3 lbs. Gel, 1 lbs. bulls, released plug.
& followed w/ 100 lbs. cement w/ 500 pounds pressure.

Remarks: Cemented By Allied Cementing Co. Inc. of Great Bend, Ks.

I hereby certify that the above plugging instructions were given as herein stated
and that I (did / ~~did not~~) observe this plugging.

Signed [Signature]
(TECHNICIAN)

FORM CP-2/3
Rev. 9-82

INVOICED
DATE 6-9-83
INV. NO. 4527-W