

DISTRICT CONSERVATION AGENT'S REPORT

*R*

TO:

State Corporation Commission  
Conservation Division  
800 Bitting Building  
Wichita, Kansas

FILE NO. \_\_\_\_\_

LOCATION SW-NW-SE

SEC. 26 TWP. 20 RGE. 14W

Dry Hole X Abandoned Oil Well \_\_\_\_\_ Abandoned Gas Well \_\_\_\_\_

I have today completed supervision of plugging of:

Well No. # 7 Lease Wylie

Operator Spink Oil Co Address 904 Division Nat Bank Bldg  
Wichita, Kansas

Field \_\_\_\_\_ County Barton

Total Depth 3630 Feet.

(Describe briefly the manner in which the well was plugged)

8 3/4" 446' Circulated With Cement.  
5 1/2" 3560' Cemented with 50% Plugged back 1W  
plug 357' Perforated 3537'-3564' filled with  
sand to 3530' Run 5" cement with duck  
failes. was flowing water from below surface  
plug. Halburton Pumped 20% Mud and  
22.5% Cement. 8% full of cement.  
West Supply Co Contractors  
(Ralph)

M. L. Pires  
District Conservation Agent

Date 7-19-52

RECEIVED  
STATE CORPORATION COMMISSION

JUL 21 1952 7-2152

CONSERVATION DIVISION  
Wichita, Kansas

PLUGGING  
WELL SEC 26 TWP 20 R 14W  
BOOK PAGE 31 LINE 20

*IV*