



WELL LOG

Robert E. Williams et al  
Senko #2

Sec. 19; T-20S; R-11W.  
SE SW SW  
County: Barton, Kas.

Total Depth: 3390'  
Comm: 7-7-48 Comp.: 7-17-48  
Contractor: J.D.Ferrell Drig.Co.Inc.  
Issued 7-19-48. Rotary: O-3390'

Elevation: 1805'  
Production: Dry

Casing: 250' 8 5/8" Cemented with 150 sax bulk  
cement. Cement Circulated.

Figures Indicate bottoms of formations

cellar	4
sand	190
shale & shells	520
red bed	570
anhydrite	590
red bed & shells	940
shale & shells	1080
salt & shale	1240
shale & shells	1445
sand	1460
lime & shale	1515
lime	1620
broken lime	1780
lime	1857
lime & shale	2325
shale & shells	2490
shale & lime	2595
broken lime	2620
shale	2705
broken lime	2865
lime	2885
lime & shale	2990
broken lime & shale	3085
lime & shale	3150
lime	3370
conglomerate	3390
Total Depth	3390

Tops:	
Anhydrite	570
Topeka	2712
Heebner	2970
Brown lime	3103
L.K.C.	3123
Base K.C.	3309
Conglomerate	3349
Total Depth	3390

We hereby certify this to be a correct and accurate log of the above described well as shown by the daily drilling reports.

J.D.FERRELL DRILLING COMPANY, INC.,

By: *J.D. Ferrell*

Subscribed and sworn to before me this 23rd day of July 1948

My commission Expires:

10-15-51

*Merle J. Sandberg*  
Notary Public

PLUGGING  
FILE SEC 19 T 20 R 11 W  
BOOK PAGE 45 LINE 5

