

4-071081

12-22

15.009.14425.0000

TO: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API number: 15- - 8-26-41

SE NE SW /4 SEC. 10, 20 S, 11 W  
1650 feet from S section line  
2970 feet from E section line

Operator license# 3613 Lease Panning B well # 24

Operator: Hallwood Petroleum, Inc. County Barton

Address: P.O. Box 378111 Well total depth 3288 feet  
Denver, Colorado 80237 Conductor Pipe: 0 inch @ 0 feet  
Bruce Hoffman Surface pipe 8 5/8 Inch @ 208 feet

106.86

Aband. oil well X, Gas well    , Input well    , SWD    , D & A    

Plugging contractor: Halliburton Services-Klima Well Service License#    

Address: Pratt, Kansas - Claflin, Kansas

Company to plug at: Hour: A.M. Day: 22 Month: December Year: 93

Plugging proposal received from: George Hutton - Rick Popp

Company: Hallwood Petroleum, Inc. Phone: 316-792-2756

Were: 8 5/8" - 208' S.P. cwc. w/125 sxs. cement. 5 1/2" casing set @ 3283' w/75 sxs. cement. Open hole - 3283' - 3288'. Casing good. Proposal by Dennis Hamel. 275 sxs. 60/40 pozmix-10% gel-5 sxs.hulls. Bentonite gel 12 sxs. Pump in with pump truck - spot and displace all cement and gel through tubing. Load both 5 1/2" casing and 5 1/2" x 8 5/8" annulus with 4 sxs. cement and shut in under pressure.

Plugging Proposal Received by: Dennis L. Hamel

Plugging operations attended by agent? All[ X ], Part[     ], None[     ]

Completed: Hour: 12:00P.M., Day: 22, Month: December, Year: 93

Actual plugging report: Hallwood Petroleum ordered 275 sxs. 60/40 pozmix 10% gel and 5 sxs. hulls. Pumped in with pump truck. Spotted and displaced all cement through tubing. 1) Perf. casing @ 1400' - 520' - 260'. 2) 2 7/8" tubing @ 3200' w/12 sxs. gel followed with 50 sxs. cement w/1 sx. hulls. 3) 2 7/8" tubing @ 1500' w/225 sxs. cement. Cement did not circulate. 2 sxs. hulls added. 4) Tagged cement @ 310'. 5) 2 7/8" @ 310' w/100 sxs. cement. Cement circulated out of 5 1/2" casing and 5 1/2" x 8 5/8" annulus 6) Squeezed 5 1/2" casing w/25 sxs. cement. Max. pressure 250 PSI.

RECEIVED  
STATE CORPORATION COMMISSION

1-5-94 JAN 05 1994

Remarks: Cemented by Halliburton  
Condition of casing(in hole):GOOD X BAD     Anhy.plug:YES X NO      
Bottom plug(in place):YES X ,CALC     ,NO     Dakota plug:YES X ,NO      
Plugged through TUBING X , CASING     . Elevation:     GL    

I did [ X ] / did not [     ] observe the plugging.

*Manon Schmitt*  
(agent)

INVOICED  
DATE 1-6-94  
INV. NO. 39633  
12-22