

Effective Date: 06/28/2017
District # 1
SGA? ☒ Yes ☐ No

KANSAS CORPORATION COMMISSION
OIL & GAS CONSERVATION DIVISION

1358002

Form CB-1
Oct 2016

Form must be Typed
Form must be Signed
All blanks must be Filled

CATHODIC PROTECTION BOREHOLE INTENT

Must be approved by the KCC sixty (60) days prior to commencing work.

Form KSONA-1, Certification of Compliance with the Kansas Surface Owner Notification Act, MUST be submitted with this form.

Expected Spud Date: 07/01/2017
month day year

OPERATOR: License# 35267
Name: La Grange Acquisition, LP dba Energy Transfer Company
Address 1: 1300 MAIN ST.
Address 2: _____
City: HOUSTON State: TX Zip: 77002 + ____
Contact Person: Jeremy Luck
Phone: 713-989-7232

CONTRACTOR: License# _____
Name: Advise on ACO-1 – Must be licensed by KCC or KDHE

Type Drilling Equipment: ☒ Mud Rotary ☐ Cable
☐ Air Rotary ☐ Other

Construction Features

Length of Cathodic Surface (*Non-Metallic*) Casing

Planned to be set: _____ 20 _____ feet

Length of Conductor pipe (*if any*): _____ 0 _____ feet

Surface casing borehole size: _____ 16.5 _____ inches

Cathodic surface casing size: _____ 10.5 _____ inches

Cathodic surface casing centralizers set at depths of: _____ 20 _____ ; _____ ;
_____ ; _____ ; _____ ; _____ ; _____ ; _____ ;

Cathodic surface casing will terminate at:

☐ Above surface ☐ Surface Vault ☒ Below Surface Vault

Pitless casing adaptor will be used: ☐ Yes ☒ No Depth _____ feet

Anode installation depths are: Attached _____ ; _____ ; _____ ; _____ ; _____ ;
_____ ; _____ ; _____ ; _____ ; _____ ; _____ ;

AFFIDAVIT

The undersigned hereby affirms that the drilling, completion and eventual plugging of this well will comply with K.S.A. 55-101 et. seq.

It is agreed that the following minimum requirements will be met:

1. Notify the appropriate District office prior to spudding and again before plugging the well. An agreement between the operator and the District Office on plugs and placement is necessary prior to plugging. In all cases, notify District Office prior to any grouting.
2. Notify appropriate District Office 48 hours prior to workover or re-entry.
3. A copy of the approved notice of intent to drill shall be posted on each drilling rig.
4. The minimum amount of cathodic surface casing as specified below shall be set by grouting to the top when the cathodic surface casing is set.
5. File all required forms: a. File Drill Pit Application (form CDP-1) with Intent to Drill (form CB-1). b. File Certification of Compliance with Kansas Surface Owner Notification Act (form KSONA-1) with Cathodic Protection Borehole Intent (CB-1) c. File Completion Form (ACO-1) within 60 days from spud date.
d. Submit plugging report (CP-4) within 60 days after final plugging is completed.

KCC WICHITA

JUL 26 2018

RECEIVED

For KCC Use ONLY

API # 15 - 15-129-21984-00-00

Conductor pipe required _____ feet

Minimum Cathodic Surface Casing Required: 20 feet

Approved by: Rick Hestermann 06/23/2017

This authorization expires: 06/23/2018
(This authorization void if drilling not started within 12 months of approval date.)

Spud date: _____ Agent: _____

Spot Description: _____
 SW SE SE NW Sec. 26 Twp. 33 S. R. 42 ☐ E ☒ W
 (10000) 2466 _____ feet from ☒ N / ☐ S Line of Section
 2076 _____ feet from ☐ E / ☒ W Line of Section

Is SECTION: ☒ Regular ☐ Irregular?

(Check directions from nearest outside corner boundaries)

County: Morton
 Facility Name: Mongone
 Borehole Number: 01
 Ground Surface Elevation: 3420 Estimated MSL
 Cathodic Borehole Total Depth: 350 feet
 Depth to Bedrock: 110 feet

Water Information

Aquifer Penetration: ☐ None ☒ Single ☐ Multiple
 Depth to bottom of fresh water: 110
 Depth to bottom of usable water: 380
 Water well within one-quarter mile: ☐ Yes ☒ No
 Public water supply well within one mile: ☐ Yes ☒ No
 Water Source for Drilling Operations:
☐ Well ☐ Farm Pond ☐ Stream ☒ Other

Water Well Location: _____
DWR Permit # _____ Apply If needed.

Standard Dimension Ratio (SDR) is = 26

(Cathodic surface csg. O.D. in inches / MWT in inches = SDR)

Annular space between borehole and casing will be grouted with:

☐ Concrete ☐ Neat Cement ☐ Bentonite Cement ☒ Bentonite Clay
Anode vent pipe will be set at: 0 feet above surface

Anode conductor (backfill) material TYPE: SC2

Depth of BASE of Backfill Installation material): 350

Depth of TOP of Backfill installation material: 130

Borehole will be Pre-Plugged? ☐ Yes ☒ No

If this permit has expired or will not be drilled, check a box below; sign, date and return to the address below.

☒ Permit Expired ☐ Well Not Drilled

7/26/18
Date

Signature of Operator or Agent

Signature of Operator or Agent
McLeary CP Installation

Mail to: KCC - Conservation Division, 266 N Main St, Ste 220, Wichita, KS 67202-1513