

Correct Copy

CARD MUST BE TYPED

State of Kansas

CARD MUST BE SIGNED

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 4-28-88 month day year

API Number 15-023-20,256-00-00 C-SW-SE

OPERATOR: License # 5386 Name Production Drilling, Inc. Address P.O. Box 680 City/State/Zip Hays, Ks. 67601 Contact Person Larry Patterson Phone (913) 625-1189

NW SW NW Sec 11 Twp 1 S Rg 38 3630 Ft. from South Line of Section 4950 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 8682 Name Golden Eagle Drilling City/State Box 55, McCook, NE 69001

Nearest lease or unit boundary line 330 feet County Cheyenne Lease Name Shafer Well # 1

Well Drilled For: Oil SWD Infield Mud Rotary Gas Inj Pool Ext Air Rotary OWWO Expl Wildcat Cable

Ground surface elevation feet MSL Domestic well within 330 feet: yes no Municipal well within one mile: yes no Depth to bottom of fresh water Depth to bottom of usable water 100 Surface pipe by Alternate: 1 2 X Surface pipe planned to be set 150! Conductor pipe required 4900 Projected Total Depth 4900 Formation Moral Sand

IF OWWO: old well info as follows: Operator Well Name Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications Date 4-18-88 Signature of Operator or Agent Title Pres

For KCC Use: Conductor Pipe Required feet; Minimum Surface Pipe Required 150 feet per Alt. 1

This Authorization Expires 10-20-88 Approved By RCH 4-20-88

EFFECTIVE DATE: 4-25-88 Dave Padgugall Golden Eagle 6-15-88

Set 150' spend 6-16-88 drill water well

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ Arbuckle (if penetrated) depth with 25 sxs of Cement 2nd plug @ Anhydrite feet depth with 50 sxs of Cement 3rd plug @ Base Dakota feet depth with 100 sxs of Cement 4th plug @ .50! below base of surface depth with 40 sxs of Cement 5th plug @ .40! feet depth with 10 sxs of Cement with wiper plug (2) Rathole with sxs (b) Mousehole with sxs

NOTE: Agreement between operator and district office on plug placement and the amount of cement to be used is necessary prior to plugging. In Addition: Call district office after well is either plugged or production casing is cemented in. (Call 7 a.m. to 5 p.m. workdays)

District office use only:

API # 15-023-20,256-00-00 Surface casing of feet set with sxs at hours, 19 Alternate 1 or 2 surface pipe was used. Alternate 2 cementing was completed @ ft. depth with sxs on 19 Hole plugged 19, agent

RECEIVED JUL 12 1988 07-12-1988 CONSERVATION DIVISION Wichita, Kansas

Form C-1 12/85

Received KCC District #6

APR 21 1988

Hays, KS