

1100344

TO: STATE CORPORATION COMMISSION

API NUMBER 15-175-21,380 - 0000
SW NE NE SEC. 24, T 32 S, R 34 W

CONSERVATION DIVISION - PLUGGING SECTION 4030 FEET FROM SOUTH SECTION LINE

WICHITA STATE OFFICE BLDG., 130 S. MARKET 1250 FEET FROM EAST SECTION LINE

WICHITA, KANSAS 67202

LEASE NAME DONLEY A WELL # 2

TECHNICIAN'S PLUGGING REPORT

3/28

COUNTY SEWARD 97.70

OPERATOR LICENSE # 5447

WELL TOTAL DEPTH 3006 FEET

OPERATOR: OXY USA INC

PRODUCTION CSG: SIZE 5 1/2" @ 3005' WITH 500 SX

NAME AND BOX 2528

SURFACE CASING: SIZE 8 5/8" @ 649' WITH 350 SX

ADDRESS LIBERAL, KS 67950-2528

RECEIVED
STATE CORPORATION COMMISSION

ABANDONED OIL WELL GAS WELL X INPUT WELL SWD WELL APR 10 2000 D/A

OTHER WELL AS HEREINAFTER INDICATED

PLUGGING CONTRACTOR SARGENT & HORTON PLUGGING, INC.

CONSERVATION DIVISION
LICENSE NUMBER 31151

ADDRESS RT. 1, BOX 49BA TYRONE, OK 73951-9731

COMPANY TO PLUG AT: HOUR: 8:00 AM DAY: 28 MONTH: 03 YEAR: 2000

PLUGGING PROPOSAL RECEIVED FROM DON HORTON

(COMPANY NAME) SARGENT & HORTON PLUGGING, INC. (PHONE) 580-854-6515

WERE: PERFS AT 2576-79, 2586-88, 2612-16, 2630-34, 2652-56

1ST PLUG SET 200# HULLS AND 25 SX CEMENT FROM 2576-2376. PRESSURE INCREASED TO 1200 PSI

AT DISPLACEMENT. 2ND PLUG CHECK BACKSIDE WITH 15 SX CEMENT TO 760 PSI. 3RD PLUG FILL

CASING WITH 80 SX CEMENT FROM 300' TO 0'.

PLUGGING PROPOSAL RECEIVED BY GARY WINTERS

PLUGGING OPERATIONS ATTENDED BY AGENT?: ALL X PART NONE

OPERATIONS COMPLETED: HOUR: 4:30 PM DAY: 28 MONTH: 03 YEAR: 2000

ACTUAL PLUGGING REPORT

1ST PLUG SET 200# HULLS AND 25 SX CEMENT FROM 2576-2376. PRESSURE INCREASED TO 1200 PSI

AT DISPLACEMENT. 2ND PLUG CHECK BACKSIDE WITH 15 SX CEMENT TO 760 PSI. 3RD PLUG FILL

CASING WITH 80 SX CEMENT FROM 300' TO 0'.

INVOICED

DATE 4/14/00

REMARKS: USED COMMON CEMENT BY SARGENTS. NO CASING RECOVERED.

(IF ADDITIONAL DESCRIPTION IS NECESSARY, USE BACK OF THIS FORM.)

I (DID) OBSERVE THIS PLUGGING.

SIGNED Gary Winters (TECHNICIAN)

FORM CP-2/3

Handwritten initials and signatures.