

To: 1 100078  
STATE CORPORATION COMMISSION  
Wichita State Office Bldg. - PLUGGING SECTION App.  
130 S. Market, Room 2078  
Wichita, KS 67202

API NUMBER 15- 175-21,194-0000  
W/2 SE, SEC. 25, T 32 S, R 34 W/E  
1420 feet from S section line  
1987 feet from E section line

11-12

TECHNICIAN'S PLUGGING REPORT  
Operator License # 6120  
Operator: Cabot Oil & Gas Corporation  
Name & Address: 9400 N. Broadway, Ste. 608  
Oklahoma City, OK 73114

Lease Name Hitch Well # 2-25  
County Seward 200,26  
Well Total Depth 6162 feet  
Conductor Pipe: Size 20" feet 63  
Surface Casing: Size 8 5/8" feet 1667

Abandoned Oil Well \_\_\_\_\_ Gas Well  Input Well \_\_\_\_\_ SWD Well \_\_\_\_\_ O&A \_\_\_\_\_  
Other well as hereinafter indicated \_\_\_\_\_

Plugging Contractor Sargent & Horton Plugging, Inc. License Number 31151  
Address Rt. 1, Box 49BA, Tyrone, OK 73951-9731

Company to plug at: Hour: 10 a.m. Day: 12 Month: 11 Year: 1996

Plugging proposal received from Don Horton  
(company name) Sargent & Horton Plugging, Inc. (phone) 405-854-6515

Work: 4 1/2" at 6003' with 610 sx cement, Perfs at 5608-30'  
1st plug pump 2 sx hulls and 20 sx cement on bottom,  
2nd plug at 1680' with 50 sx cement,  
3rd plug at 700' with 40 sx cement,  
4th plug at 40-0' with 10 sx cement.

Plugging Proposal Received by Gary Winters  
(TECHNICIAN)

Plugging Operations attended by Agent?: All \_\_\_\_\_ Part \_\_\_\_\_ None

Operations Completed: Hour: 4 p.m. Day: 12 Month: 11 Year: 19 96

ACTUAL PLUGGING REPORT 1st plug pumped 2 sx hulls and 20 sx cement at 5730-5500',  
2nd plug at 1680' with 50 sx cement,  
3rd plug at 700' with 40 sx cement,  
4th plug at 40-0' with 15 sx cement.

11-14-96

RECEIVED  
NOV 14 1996  
MAILS & CO.

Remarks: Used common cement by Sargent & Horton. Recovered 2525' of 4 1/2" casing.  
(If additional description is necessary, use BACK of this form.)

INVOICED  
NOV 15 1996  
observe this plugging.

Signed Gary Winters  
(TECHNICIAN)

DATE \_\_\_\_\_  
INV. NO. 46980