

1060836

To: STATE CORPORATION COMMISSION  
CONSERVATION DIVISION - PLUGGING SECTION  
200 COLORADO DERBY BUILDING  
WICHITA, KANSAS 67202

API NUMBER 15- 185-22,359-0000  
N/2 SW SW, SEC. 28, T 23 S, R 13 W/E  
990 feet from S section line  
4620 feet from E section line

TECHNICIAN'S PLUGGING REPORT

Operator License # 5020  
Operator: Rine Exploration Company  
Name & Address: 300 W. Douglas, Suite 645  
Wichita, KS 67202

Lease Name O'Connor Well # 1-28  
County Stafford 144.30  
Well Total Depth 4440 Arbuckle feet  
Conductor Pipe: Size feet  
Surface Casing: Size 8 5/8 feet 379

Abandoned Oil Well Gas Well Input Well SWD Well D&A X

Other well as hereinafter indicated

Plugging Contractor Duke Drilling Co., Inc. License Number 5929  
Address 620 Hubbard, Box 823, Great Bend, KS 67530

Company to plug at: Hour: 4:30 pm Day: 15 Month: March Year: 19 86

Plugging proposal received from Leonard Williamson

(company name) Duke Drilling (phone) 316-793-8366

were: to fill hole with heavy mud and spot cement through drill pipe Elevation 1900' KB  
Anhydrite 781-805'

1st plug in the Arbuckle with 40 sx cement if 50' or more

2nd plug at the base of the Anhydrite with 50 sx cement

3rd plug 30' below the base of the surface pipe with 40 sx cement  
solid bridge

4th plug hulls - plug at 40' -- cement to surface with 10 sx cement

6th plug to circulate rat hole with 15 sx cement. Plug water well from bottom to top  
with cement (10 sx) Plugging Proposal Received by Paul A. Luthi  
(TECHNICIAN)

Plugging Operations attended by Agent?: All Part None X

Operations Completed: Hour: 8:45 pm Day: 15 Month: March Year: 19 86

ACTUAL PLUGGING REPORT 1st plug at 3984' with 40 sx cement, 2nd plug at 805' with 50 sx  
cement, 3rd plug at 410' with 40 sx cement, 4th & 5th plugs - solid bridge - hulls -

plug at 40' -- cement to surface with 10 sx cement, 6th plug to circulate rat hole with  
15 sx cement. Plugged water well with 10 sx cement.

STATE CORPORATION COMMISSION

3-20-86 MAR 20 1986

Remarks: Used 60/40 Pozmix 6% gel by Allied. CONSERVATION DIVISION  
Wichita, Kansas

If additional description is necessary, use BACK of this form.)

INVOICED

(if not observed, did not) observe this plugging.

DATE MAR 20 1986

Signed Paul A. Luthi  
(TECHNICIAN)

INV. NO. 13033  
3-15

NOTICE OF INTENTION TO DRILL

(see rules on reverse side)

Starting Date 03/07/86 month day year

API Number 15-185-22,359-0000

OPERATOR: License # 5020
Name Rine Exploration Company
Address Suite #645, 300 W. Douglas
City/State/Zip Wichita, KS 67202
Contact Person M. Bradford Rine
Phone 316/262-5418

N 1/2 SW 1/4 SW 1/4 Sec. 28 Twp. 23 S, Rg. 13
990 Ft. from South Line of Section
4620 Ft. from East Line of Section

(Note: Locate well on Section Plat on reverse side)

CONTRACTOR: License # 5929
Name Duke Drilling Co., Inc.
City/State Wichita, KS 67202

Nearest lease or unit boundary line 660 feet
County Stafford

Lease Name O'Connor Well # 1-28
Ground surface elevation 1895 L&S feet MSL

Well Drilled For: Well Class: Type Equipment:
X Oil SWD Infield X Mud Rotary
X Gas Inj Pool Ext Air Rotary
OWWO Expl X Wildcat Cable

Domestic well within 330 feet: yes X no
Municipal well within one mile: yes X no

Depth to bottom of fresh water 100
Depth to bottom of usable water 200 250

Surface pipe by Alternate: 1 X 2
Surface pipe planned to be set 360

Conductor pipe required 0
Projected Total Depth 4050 feet
Formation Arbuckle

If OWWO: old well info as follows:

Operator
Well Name
Comp Date Old Total Depth

I certify that well will comply with K.S.A. 55-101, et seq., plus eventually plugging hole to KCC specifications.

Date 02/27/86 Signature of Operator or Agent M. Bradford Rine Title President / Geologist

For KCC Use:

Conductor Pipe Required feet; Minimum Surface Pipe Required 250 feet per Alt (1) X
This Authorization Expires 8-28-86 Approved By 2-28-86 R

move July-86 set 360' of pipe/100' note

N 1/2 SW 1/4 SW 1/4 Sec. 28 Twp. 23 S, Rg. 13 East X West

PLUGGING PROPOSAL IF ABOVE IS D & A

This plugging proposal will be reviewed and approved or revised at the time the district office is called prior to setting surface casing (call 7 a.m. to 5 p.m. workdays).

1st plug @ 3990 feet depth with 40 sxs of 60-40 poz mix - 6% gel
2nd plug @ 800 feet depth with 40 sxs of 60-40 poz mix - 6% gel
3rd plug @ 390 feet depth with 50 sxs of 60-40 poz mix - 6% gel
4th plug @ 0-40 w/solid bridge feet depth with 10 sxs of 60-40 poz mix - 6% gel
5th plug @ feet depth with sxs of
(2) Rathole with circulate 15 sxs
(2) Mousehole with circulate 10 sxs

STATE CORPORATION COMMISSION

MAR 20 1986

CONSERVATION DIVISION
Wichita, Kansas

PUSHER TD 44 40 FORMATION Arbuckle
SURFACE PIPE 8 5/8 @ 379
ANHYDRITE 80.5 ELEVATION 1900 H
STARTING TIME & DATE 3-15-86 4:30 PM
PLETION TIME & DATE 3-15-86 8:45 PM
1st PLUG @ 3984 FT. W/ 40 SX
2nd PLUG @ 805 FT. W/ 50 SX
3rd PLUG @ 410 FT. W/ 40 SX
4th PLUG @ 40-0 FT. W/ 10 SX
RAT HOLE CIRCULATED W/ 15 SX
MOUSE HOLE CIRCULATED W/ SX
WATER WELL PLUGGED W/ 10 SX

CEMENT COMPANY Allied 60/40 w/ 6% gel
TECHNICIAN Leather
Arbuckle in 40 sxs
any w/ 60 sxs
30' out surf 40
40'-0' SB-10 sxs
Water well 10 sxs
Cir 15 sxs not
60/40 w/ 6%