Confidentiality Requested:

CORRECTION #1

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION 1234562

Form ACO-1 August 2013 Form must be Typed Form must be Signed All blanks must be Filled

WELL COMPLETION FORM WELL HISTORY - DESCRIPTION OF WELL & LEASE

OPERATOR: License #	API No. 15				
Name:	Spot Description:				
Address 1:					
Address 2:	Feet from Dorth / South Line of Section				
City: State: Zip:+	Feet from East / West Line of Section				
Contact Person:	Footages Calculated from Nearest Outside Section Corner:				
Phone: ()					
CONTRACTOR: License #	GPS Location: Lat:, Long:				
Name:	(e.g. xx.xxxx) (e.gxxx.xxxx)				
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84				
Purchaser:	County:				
Designate Type of Completion:	Lease Name: Well #:				
New Well Re-Entry Workover	Field Name:				
	Producing Formation:				
	Elevation: Ground: Kelly Bushing:				
□ OG □ GSW □ Temp. Abd.	Total Vertical Depth: Plug Back Total Depth:				
CM (Coal Bed Methane)	Amount of Surface Pipe Set and Cemented at: Feet				
Cathodic Other (Core, Expl., etc.):	Multiple Stage Cementing Collar Used?				
If Workover/Re-entry: Old Well Info as follows:	If yes, show depth set: Feet				
Operator:	If Alternate II completion, cement circulated from:				
Well Name:	feet depth to:w/sx cmt.				
Original Comp. Date: Original Total Depth:					
Deepening Re-perf. Conv. to ENHR Conv. to SWD	Drilling Fluid Management Plan				
Plug Back Conv. to GSW Conv. to Producer	(Data must be collected from the Reserve Pit)				
	Chloride content: ppm Fluid volume: bbls				
Commingled Permit #: Dual Completion Permit #:	Dewatering method used:				
SWD Permit #:	Location of fluid disposal if hauled offsite:				
ENHR Permit #:					
GSW Permit #:	Operator Name:				
	Lease Name: License #:				
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West				
Recompletion Date Recompletion Date	County: Permit #:				

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY								
Confidentiality Requested								
Date:								
Confidential Release Date:								
Wireline Log Received								
Geologist Report Received								
UIC Distribution								
ALT I II III Approved by: Date:								

CORRECTION #1

1234562

Operator Nar	me:			Lease Name:	_ Well #:
Sec	Twp	_S. R	East West	County:	

INSTRUCTIONS: Show important tops of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed.

Final Radioactivity Log, Final Logs run to obtain Geophysical Data and Final Electric Logs must be emailed to kcc-well-logs@kcc.ks.gov. Digital electronic log files must be submitted in LAS version 2.0 or newer AND an image file (TIFF or PDF).

Drill Stem Tests Taker (Attach Additional	Yes No		-	tion (Top), Depth an		Sample	
Samples Sent to Geo	logical Survey	Yes No	Nam	е		Тор	Datum
Cores Taken Electric Log Run		☐ Yes ☐ No ☐ Yes ☐ No					
List All E. Logs Run:							
		CASING Report all strings set-c	RECORD Ne		ction, etc.		
Purpose of String	Size Hole Drilled	Size Casing Set (In O.D.)	Weight Lbs. / Ft.	Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
	<u> </u>	ADDITIONAL	CEMENTING / SQL	JEEZE RECOR	D		
Purpose: Perforate	Depth Top Bottom	Type of Cement	# Sacks Used	Type and Percent Additives			
Protect Casing Plug Back TD							
Plug Off Zone							
Did you perform a hydraulic fracturing treatment on this well? Does the volume of the total base fluid of the hydraulic fracturing treatment exceed 350,00 Was the hydraulic fracturing treatment information submitted to the chemical disclosure re-				Yes Yes Yes Yes	No (If No, skip	o questions 2 an o question 3) out Page Three	
Shots Per Foot		ON RECORD - Bridge Plug Footage of Each Interval Perl			racture, Shot, Cement Amount and Kind of Mai		d Depth

		Flowing	Pump	ing 🔄 Gas Lift	Other (Explain)		
Estimated Production Per 24 Hours	0		Mcf	Water	Bbls.	Gas-Oil Ratio	Gravity
DISPOSITION OF GAS:		METHOD OF COMPLETION:			PRODUCTION INTER	RVAL:	
Vented Sold Used on Lease		Open Hole Perf. Dually Comp. (Submit ACO-5)		Commingled (Submit ACO-4)			
(If vented, Submit ACO-18.	3.)	Other (Specify)					

Packer At:

Liner Run:

No

Yes

TUBING RECORD:

Size:

Date of First, Resumed Production, SWD or ENHR.

Set At:

Producing Method:

Form	ACO1 - Well Completion
Operator	Unit Petroleum Company
Well Name	Haw 22 #1H
Doc ID	1234562

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	28	16	65	160	Common	144	
Intermedia te	12.25	9.625	36	1530	A	605	2% CC + 1/4# celloflake
Intermedia te	8.75	7	26	4336	A	160	5% Gyp + 10% salt
Production	6.125	4.50	11.6	8857	50/50 Poz	550	.2% SASL + 1/4# celloflake
Production	6.125	5.50	17	8857	50/50 Poz	550	.2% SASL + 1/4# celloflake

Summary of Changes

Lease Name and Number: Haw 22 #1H API/Permit #: 15-155-21700-01-00 Doc ID: 1234562 Correction Number: 1 Approved By: NAOMI JAMES

Field Name	Previous Value	New Value
Approved Date	10/09/2014	12/09/2014
Save Link	//kcc/detail/operatorE ditDetail.cfm?docID=12	//kcc/detail/operatorE ditDetail.cfm?docID=12
Well Type	23960 GAS	34562 OIL



1223960

Confidentiality Requested:

CONFIDENTIAL

KANSAS CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION

August 2013 Form must be Typed Form must be Signed All blanks must be Filled

Form ACO-1

WELL COMPLETION FORM

OPERATOR: License #	API No. 15					
Name:	Spot Description:					
Address 1:						
Address 2:	Feet from Dorth / South Line of Section					
City: State: Zip:+	Feet from East / West Line of Section					
Contact Person:	Footages Calculated from Nearest Outside Section Corner:					
Phone: ()						
CONTRACTOR: License #	GPS Location: Lat:, Long:					
Name:	(e.g. xx.xxxx) (e.gxxx.xxxx)					
Wellsite Geologist:	Datum: NAD27 NAD83 WGS84					
Purchaser:	County:					
Designate Type of Completion:	Lease Name: Well #:					
New Well Re-Entry Workover	Field Name:					
	Producing Formation:					
	Elevation: Ground: Kelly Bushing:					
Gas D&A ENHR SIGW	Total Vertical Depth: Plug Back Total Depth:					
OG GSW Temp. Abd. CM (Coal Bed Methane)	Amount of Surface Pipe Set and Cemented at: Feet					
Cathodic Other (Core, Expl., etc.):	Multiple Stage Cementing Collar Used?					
If Workover/Re-entry: Old Well Info as follows:	If yes, show depth set: Feet					
Operator:	If Alternate II completion, cement circulated from:					
	feet depth to:w/sx cmt.					
Original Comp. Date: Original Total Depth:						
Deepening Re-perf. Conv. to ENHR Conv. to SWD	Drilling Fluid Management Plan					
Plug Back Conv. to GSW Conv. to Producer	(Data must be collected from the Reserve Pit)					
Commingled Permit #:	Chloride content: ppm Fluid volume: bbls					
Commingled Permit # Dual Completion Permit #:	Dewatering method used:					
SWD Permit #:	Location of fluid disposal if hauled offsite:					
ENHR Permit #:	Location of huid disposa in natied offsite.					
GSW Permit #:	Operator Name:					
	Lease Name: License #:					
Spud Date or Date Reached TD Completion Date or	Quarter Sec TwpS. R East West					
Recompletion Date Recompletion Date	County: Permit #:					

AFFIDAVIT

I am the affiant and I hereby certify that all requirements of the statutes, rules and regulations promulgated to regulate the oil and gas industry have been fully complied with and the statements herein are complete and correct to the best of my knowledge.

Submitted Electronically

KCC Office Use ONLY								
Confidentiality Requested								
Date:								
Confidential Release Date:								
Wireline Log Received								
Geologist Report Received								
UIC Distribution								
ALT I II III Approved by: Date:								

KOLAR Document ID: 1223960

Operator Name:				Lease Name:	Well #:
Sec	Twp	S. R	East West	County:	

Page Two

INSTRUCTIONS: Show important tops of formations penetrated. Detail all cores. Report all final copies of drill stems tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface test, along with final chart(s). Attach extra sheet if more space is needed.


Final Radioactivity Log, Final Logs run to obtain Geophysical Data and Final Electric Logs must be emailed to kcc-well-logs@kcc.ks.gov. Digital electronic log files must be submitted in LAS version 2.0 or newer AND an image file (TIFF or PDF).


Drill Stem Tests Taken (Attach Additional Sheets)		Y	es 🗌 No			og Formatio	n (Top), Depth	and Datum	Sample
·	*		és 🗌 No	Ν	lame	e		Тор	Datum
Samples Sent to Geological Survey Cores Taken Electric Log Run Geologist Report / Mud Logs List All E. Logs Run:			ies No ies No ies No						
		Repo	CASING I] Ne	w Used rmediate, productio	on, etc.		
Purpose of String Size Hole Drilled			ze Casing tt (In O.D.)	Weight Lbs. / Ft.		Setting Depth	Type of Cement	# Sacks Used	Type and Percent Additives
			ADDITIONAL	CEMENTING /	SQU	EEZE RECORD			
Purpose: Depth Top Bottom Perforate Top Bottom Protect Casing Plug Back TD Plug Back TD Plug Off Zone		Туре	e of Cement	# Sacks Used		Type and Percent Additives			
 Did you perform a hydra Does the volume of the is Was the hydraulic fractu Date of first Production/Inj 	total base fluid of the h ring treatment informa	nydraulic fra tion submit	acturing treatment	al disclosure regis	-	Yes Yes Yes Yes	No (If No, s	kip questions 2 ar kip question 3) ill out Page Three	
Injection:			Flowing	Pumping		Gas Lift 🗌 O	ther <i>(Explain)</i>		
Estimated Production Per 24 Hours	Oil	Bbls.	Gas	Mcf	Wate	er Bb	ls.	Gas-Oil Ratio	Gravity
DISPOSITION	I OF GAS:		M	ETHOD OF COM	IPLE	TION:			ON INTERVAL:
Uvented Sold Used on Lease Open Hole P (If vented, Submit ACO-18.)			-		mingled	Тор	Bottom		
		Bridge Plug Type	Bridge Plug Set At		Acid,		ementing Squeeze		
TUBING RECORD:	Size:	Set At:		Packer At:					

Form	ACO1 - Well Completion
Operator	Unit Petroleum Company
Well Name	Haw 22 #1H
Doc ID	1223960

Casing

Purpose Of String	Size Hole Drilled	Size Casing Set	Weight	Setting Depth	Type Of Cement	Number of Sacks Used	Type and Percent Additives
Surface	28	16	65	160	Common	144	
Intermedia te	12.25	9.625	36	1530	A	605	2% CC + 1/4# celloflake
Intermedia te	8.75	7	26	4336	A	160	5% Gyp + 10% salt
Production	6.125	4.50	11.6	8857	50/50 Poz	550	.2% SASL + 1/4# celloflake
Production	6.125	5.50	17	8857	50/50 Poz	550	.2% SASL + 1/4# celloflake







P.O. Box 1570, Woodward, OK 73802 Ph. 580-254-5400 Fax 580-254-3242

CEMENTING REPORT

Operator: Unit Cor	poration
Well Name: Haw 22	2-1H
Legal Description:	Reno Cnty, KS

Cement Casing Data	
Cementing Date	6/13/14
Size of Drill Bit (Inches)	28
Size of Casing (Inches O.D.)	16
Setting Depth of Casing (ft.) from ground level	160
Type of Cement	Common Cement
Sacks of Cement Used	144
Was cement circulated?	Yes

Jeff M. Owen Mid-Continent Conductor, LLC



TREATMENT REPORT

Customor				,	Lease	No.					Date				-	
	nir Pe	2110	rum		Well #						Juio	6-	23	-200	4	
Field Order #		n 🦨	2			12		8512	Depth	1.000	Count		and the second second second		Sta	ite
Type Job		P		+11	Ks.			Form	ation	1530		<u> </u>	enco Legal De	escription		
C C	NW/	SUr	FSIT							TD-13	25		Logui Di	ounption	15-,	25-10
	E DATA		PERI	FORA	FING DAT	A	FLUID	USED			-	TREA	TMENT	RESUM	Ξ	
Casing Size/	Tubing Si	ze	Shots/F	-t			Acid				RATE	PRE	SS	ISIP		
Depth/530	Depth		From		То		Pre Pad			Max				5 Min.		
Volume /1 8	Volume		From		То		Pad			Min				10 Min.		
Max Press	Max Pres	S	From		То		Frac			Avg				15 Min.		
Well Connection	n Annulus V	/ol.	From		То					HHP Used				Annulus	Pressu	Ire
Plug Depth	Packer De	epth	From		То		Flush			Gas Volum	10			Total Loa	ıd	
Customer Repr	resentative				Sta	tion M	lanager Ke	un Go	()	ley	Trea	ter D	Grin	Frs	nici	100
Service Units	27283	198	885	158	43/150	\$31				19818						
Driver Names	Darin	E		Ea	DS	10	DSIP	DSIC		Dsie						
Time	Casing Pressure		bing ssure	Bbls	. Pumped		Rate					Servi	ce Log			
3:30								on	6	Chrion ,	1sel	Cerr	Mee	tins		
	200				3		4	PUN	10	3 661	s h	1926	Ph			
	200			14	143		4		Mup 32550 A-Con							
	200			6	60		4	250 Sr Common								
								Shu		laun						
										Pive	5					
	200			2	3		4	549	12	Dispis	see M	en	L			
6	00			1	00		3	Slau	P.q	ke						
1	600			11	0		3			Plus						
							*	Flos	1	Itel	1					
										,						
								Circ	019	84 35	- 65	sk	Pit			
								Joh	a	Umple	10/	DSI	inde	rec		
										,						
								the	sn	K KOU	11)					
									1.1		8. ¹					
10244	NE Hiwa	iy 6	1 • P.	О. Во	ox 8613	• P	ratt, KS 6	7124-8	613	8 • (620)	672-	120	• Fax	(620) 6	72-5	383

Taylor Printing, Inc. 620-672-3656



TREATMENT REPORT

Customer	NIT	1	DetR	Olon	2	ease No.						Date				
	HAW		-1_/V	-rur		Vell #_/	H					1	07	101	114	e
ield Order #	Statio	n Pk	2AH	L				Casing	11	Dept	336'	Count	Rei	10		State
Type Job	2 7'	"	IW	REN	ne	DAT	E		For	natior	1			Legal D	escription	10
PIPE	DATA		PER	FORA	TING	DATA		FLUID	USED			-	TREA	MENT	RESUME	1
asing Size /	Tubing Si	ze	Shots/F	=t			Acid					RATE	PRE	SS	ISIP	
epth/334	Depth		From		То		Pre P	ad			Max				5 Min.	
lume7/	Volume		From		To		Pad				Min				10 Min.	
Press	Max Pres		From		То		Frac				Avg				15 Min.	
Sopnection			From		То						HHP Used				Annulus	Pressure
g Repth	Packer De	epth	From		То		Flush				Gas Volun	1			Total Loa	d
stomer Repr	esentative					Station	Manag	er DAu	c Sc	off		Trea	ter	hard	Un	$\mathbf{)}$
	7900	199	159	205	10 1	7093	-9 1	9528						~		
iver mes	ullin	C	Siger bing	D		Phy	e									
states in the second	Casing Pressure		essure	Bbls	. Pum	ped	Ra	nte					Servic	e Log		
:15									ON	400	Soft	y n	1-00	2		
													/			
1.											2					
4:00					5		گ	:5	1+	A	eneer	2				
					12				mu		7/24					
(5				SPA							
					10		4	15		~					15 PP	0.
-)					40				yrel) /,	43 6	.01	nc/s	E	·	
/ /									Cm7	0	MIX-e	22	201	du	sel	
									12el	are	Huy					
	0.00				0.	_	-	5.5	Nº C	ng	Do					
	200				20		4	6	77		7.)				
:00 1	200				11		7	6	The	a	ls.	1)	AL	Velo	0	
									jai	em	_/ >1	410	nor ,	210	fe-	
											50	13 /	-	011	0	
											24		o m	Prot	¥ _	
									an a		/	The	F	~		
											- /	in	F)	
													V			
10244 N	JE Hiwa	av 6	1 • P.	0. B	ox 8	613 •	Pratt.	KS 67	7124-	8613	3 • (620)	672-	1201	• Fax	(620) 6	72-5383

Taylor Printing, Inc. 620-672-3656



TREATMENT REPORT

Customer U	Customer Unit Petroleym			Le	ase No	•					Date						
Lease	Hq	'w/	CUP	<u> </u>	Ŵ	^{ell #} 2	2-	11-1		<u>1999 - 1999 - 1999 - 1999 - 1999</u>				7-8	7-14		
Field Order I	n 769 Statio	on Pra	177					Casing	41/2	Depti	h	Count		no		Stat	te/55
Type Job	MW			IER					Fo	rmation	I			Legal D	escription	15:2	25-16
PIPI	E DATA			ORATI		DATA	Ι	FLUID	USED		1		TREA	TMENT	RESUM		na an a
Casing Size	Tubing S	ize S	Shots/F	t			Acid				RATE PRE				3 ISIP		
 Depth 8 8 5 7	Depth		rom		Го	A Thillie (A ship a s a	Pre F	Pad	Мах						5 Min.		- Angeler and a second seco
Volume/68	Volume		rom		To Pad						Min				10 Min.	Bindrephonisch/costactum	
Max Press	Max Pres	is	rom		Frac				*****	Avg				15 Min.			
Well Connection	on Annulus	101	rom		ō						HHP Used				Annulus	Pressu	re
Plug Depth					 o	9(1));	Flust	1			Gas Volum	e	, and a second secon		Total Loa	ıd	H Têrkiyê yer kuşûkyer kaleyê dir.
Customer Rep	stomer Representative				Τ	Station	Manaç	jer				Trea	iter				
Service Units	33708	209	20 -	19960	, ;	21010	1	9826	1986	0-1	vilis inden staande de formingele aanverse soor	284	143		X-1	Ignal	
Driver Names	50	077		į	TA	CK		A	Beni			50	re		Hysi	m	
Time	Casing Pressure	Tubi Press		Bbls. P	ump	ed	R	ate	Γ			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Servi	ce Log		hinda for exemploined and	
0930									ON.	101,1	I safer	YN	n e et	ing			
					(10-Definitions)				Bun 125 JTS 41/2 @ 11.6#								
								1311 1312 1411 1410 1410 1410 1410 1410 1410 14	Bui	2 95	5 575 5	1/2	p	17#			
				- Midmina.relies incurcas, autoura	in a constant of the		*************		Hoo	KyP	TO STO	<u>77 v</u>	TUB	<u></u>			
1100	Ø				5		6		HZO	sf	gcen		~~~~~			No. 10 Contractor of Contractor	
10.00.00.00.00.00.00.00.00.00.00.00.00.0					2 6			W 10/10/2000 (1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/	myd flysh								THE PARTY AND AND AND AND
	500			£	<u> </u>		6		Hai	0 S	Pacen	na filmenta antina a			****		
	- 0.0			149	3		b		Mi		550 5 <u>/</u> 5		0/5	OPOZ	<u>e /</u>	3. Bi	#
· .	700						0		<u>A</u>	<u>549 i</u>	<u>ar 1-12</u>	0		<u>A.</u>	****	644441000000000000000000000000000000000	
145			<u> </u>		r Gr		Ø		<u>Sh</u>	<u>yř k</u>	Down	Yel.	Cast	PLy	<u>ş</u>		
<u> </u>	0			l			6		51	<u>rr</u>	HZO D	SP	wii	<u>% Sy</u>	<u>gar H</u>	<u>20 f</u>	KLL
	600		-+	40										0	etre-mananlandaritations		
-	3000			160			5		SLOU DI	<u>v ()</u>	are are						
Ŕ	ner			167			_6	/	PLI	<u>14</u>	Down			Cold Call and a state of the st	alfaldan maran ana dadaa dadaa ahiy		
		****			kä ti se da ta ta fasi		******		PSI	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	PTOY	NN		0 000	0/		40%354
									14	<u>- </u>	10 9	000	2 12	<u> </u>	PLY)	
					****		*****			***			******			hendersenne berfinderen bekenne Frederingen er son	
mennindaturun antara metanagi da da da		****		Cathorn State State State						JB	ComP Thu	121	1	alla ka	na gali yana ya dali niyogo yangi mu fanta kana		
									nonnennen de		Thu	nK	VOU				Manada Adorgi va se da Statistica da Statistica da Statistica da Statistica da Statistica da Statistica da Stat
												/	JV	l			
10244	NE Hiwa	ay 61	• P.0	D. Box	86	13 • 1	Pratt	, KS 67	/124-	8613	8 • (620)	672-	1201	• Fax	(620) 6	72-5	383

Taylor Printing, Inc. 620-672-3656

Unit Petroleum

Reno County, Kansas [NAD 83] Section 22 T25S-R10W Haw 22 #1H


Sidetrack 1

Design: Sidetrack 1

Standard Survey Report

08 July, 2014







a subband	Unit Petroleum Reno County, Kar	isas [NAD 83]		Local Co- TVD Refe	ordinate Reference:	rence:	Well Haw 22 # 14' KB @ 1756	1H 6.00usft (UDI 331	1)
Site:	Section 22 T25S-F	R10W		MD Refer	ence:		14' KB @ 1756	6.00usft (UDI 331	1)
Well:	Haw 22 #1H			North Ref	ference:		Grid		
Wellbore:	Sidetrack 1			Survey Ca	alculation Met	hod:	Minimum Curv	ature	
Design:	Sidetrack 1			Database	:		EDM 5000.1 S	ingle User Db	
Project	Reno County	, Kansas [NAD 8	3]			KAVENIEN VARADA			
Map System: Geo Datum:	US State Plane North Americar	Datum 1983		System					
Map Zone:	Kansas Southe	ern Zone					Using geodetic	c scale factor	
Site	Section 22 T2	25S-R10W							
Site Position:			Northing:	1,7	50,023.00 usf	Latitude:			37° 52' 7.214
From:	Мар		Easting:	1,3	39,200.00 usf	Longitud	e:		98° 24' 24.933
Position Uncertain	ty:		Slot Radius:		13-3/16 "	-	vergence:		0.06 °
Well	Haw 22 #1H								
Well Position	+N/-S	0.00 usft	Northing:		1,750,023	.00 usft	Latitude:		37° 52' 7.214
	+E/-W	0.00 usft	Easting:		1,339,200		Longitude:		98° 24' 24.933
Position Uncertaint	ty	0.00 usft	Wellhead Ele	evation:			Ground Level:		1,742.00 u
Wellbore	Sidetrack 1								
	Model Na		Sample Date	Deal	lination		-	Pt-14	0(
Magnetics	Model Ma	me				U	ip Angle	Field	Strength
			Sample Date		(°)		(°)		(nT)
	IGI	RF2010	6/27/2014				(°) 65.75		(nT) 52,020
Design	IGI Sidetrack 1				(°)				
Design Audit Notes:					(°)				
Audit Notes: Version:		RF2010	6/27/2014 Phase:	ACTUAL	(°) 4.57		65.7		
Audit Notes:	Sidetrack 1	RF2010	6/27/2014 Phase: om (TVD)		(°) 4.57		65.7		52,020
Audit Notes: Version:	Sidetrack 1	RF2010 Depth Fro	6/27/2014 Phase: om (TVD)	ACTUAL +N/-S (usft)	(°) 4.57	Tie On Depth: +E/-W	65.7	5 Direction (°)	52,020
Audit Notes: Version: Vertical Section:	Sidetrack 1	RF2010 Depth Fro	6/27/2014 Phase: om (TVD) ft) 0.00	ACTUAL +N/-S (usft)	(°) 4.57	Tie On Depth: +E/-W (usft)	65.7	5 Direction (°)	52,020
Audit Notes: Version: Vertical Section: Survey Program From	Sidetrack 1 1.0 To	RF2010 Depth Frc (us Date 7/7/201	6/27/2014 Phase: om (TVD) ft) 0.00	ACTUAL +N/-S (usft) 0.	(°) 4.57	Tie On Depth: +E/-W (usft)	65.7	5 Direction (°)	52,020
Audit Notes: Version: Vertical Section: Survey Program From (usft)	Sidetrack 1 1.0 To (usft)	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor	6/27/2014 Phase: om (TVD) ft) 0.00	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name	Tie On Depth: +E/-W (usft)	65.7	5 Direction (°) 18	52,020
Audit Notes: Version: Vertical Section: Survey Program From	Sidetrack 1 1.0 To (usft) 3 3,089.00 1	RF2010 Depth Frc (us Date 7/7/201	6/27/2014 Phase: pm (TVD) ft) 0.00 4	ACTUAL +N/-S (usft) 0.	(°) 4.57	Tie On Depth: +E/-W (usft)	65.7	5 Direction (°) 18 rd	52,020
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00	Sidetrack 1 1.0 To (usft) 3 3,089.00 1	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor WWD (OH)	6/27/2014 Phase: pm (TVD) ft) 0.00 4	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD	Tie On Depth: +E/-W (usft)	65.74 Description MWD - Standa	5 Direction (°) 18 rd	52,020
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00	Sidetrack 1 1.0 To (usft) 3 3,089.00 1	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor WWD (OH)	6/27/2014 Phase: pm (TVD) ft) 0.00 4 e) etrack 1)	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD	Tie On Depth: +E/-W (usft) 0.00	65.74 Description MWD - Standa MWD - Standa	5 Direction (°) 18 rd rd	52,020 3,089.00 0.36
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00	Sidetrack 1 1.0 To (usft) 3 3,089.00 1 8,900.00 3 Inclination	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor WWD (OH) Sidetrack 1 (Side Azimuth	6/27/2014 Phase: pm (TVD) ft) 0.00 4	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD MWD	Tie On Depth: +E/-W (usft) 0.00	Description MWD - Standa MWD - Standa	5 Direction (°) 18 rd rd rd Build Rate	52,020 3,089.00 0.36 Turn Rate
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft)	Sidetrack 1 1.0 To (usft) : 3,089.00 1 8,900.00 : Inclination (°)	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor VIVVD (OH) Sidetrack 1 (Side Azimuth (°)	6/27/2014 Phase: om (TVD) (TVD) 0.00 4 e) otrack 1) Vertical Depth (usft)	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD MWD +E/-W (usft)	Tie On Depth: +E/-W (usft) 0.00	Description MWD - Standa MWD - Standa MWD - Standa	5 Direction (°) 18 rd rd Rate (°/100usft)	52,020 3,089.00 0.36 Turn Rate (°/100usft)
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00	Sidetrack 1 1.0 To (usft) 3 3,089.00 1 8,900.00 3 Inclination (°) 0.00	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor VIVVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00	6/27/2014 Phase: om (TVD) (TVD) 0.00 4 e) vertical Depth (usft) 0.00	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD MWD +E/-W (usft) 0.00	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00	Description MWD - Standa MWD - Standa MWD - Standa	5 Direction (°) 18 I8 I8 I8 I8 I8 I8 I8 I8 I8 I8 I8 I8 I8	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00	Sidetrack 1 1.0 To (usft) : 0 3,089.00 1 8,900.00 3 Inclination (°) 0.00 0.63	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor VIVVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46	6/27/2014 Phase: om (TVD) (TVD) 0.00 4 e) vertical Depth (usft) 0.00 100.00	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD MWD +E/-W (usft) 0.00 0.53	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14	Description MWD - Standa MWD - Standa MWD - Standa (*/100usft) 0.00 0.63	5 Direction (°) 18 18 18 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 0.36 Turn Rate (*/100usft) 0.00 0.00
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 iurvey Measured Depth (usft) 0.00 100.00 200.00	Sidetrack 1 1.0 To (usft) :: 0 3,089.001 8,900.00 : Inclination (°) 0.00 0.63 0.92	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor VIVVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46 123.98	6/27/2014 Phase: om (TVD) (TVD) 0.00 4 e) vertical Depth (usft) 0.00 100.00 199.99	ACTUAL +N/-S (usft) 0. +N/-S (usft) 0.00 -0.15 -0.74	(°) 4.57 00 Tool Name MWD MWD +E/-W (usft) 0.00 0.53 1.73	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14 0.73	Description MWD - Standa MWD - Standa MWD - Standa MWD - Standa	5 Direction (°) 18 18 18 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00 0.00 18.52
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00	Sidetrack 1 1.0 To (usft) : 0 3,089.00 1 8,900.00 : 1nclination (°) 0.00 0.63 0.92 0.90	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor VIVVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46	6/27/2014 Phase: om (TVD) (TVD) 0.00 4 e) vertical Depth (usft) 0.00 100.00	ACTUAL +N/-S (usft) 0.	(°) 4.57 00 Tool Name MWD MWD +E/-W (usft) 0.00 0.53	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14	Description MWD - Standa MWD - Standa MWD - Standa (*/100usft) 0.00 0.63	5 Direction (°) 18 18 18 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 0.36 Turn Rate (*/100usft) 0.00 0.00
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00 200.00 300.00 400.00	Sidetrack 1 1.0 To (usft) : 3,089.00 1 8,900.00 3 Inclination (°) 0.00 0.63 0.92 0.90 0.90	RF2010 Depth Fro (us) Date 7/7/201 Survey (Wellbor WVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46 123.98 112.09 110.53	6/27/2014 Phase: pm (TVD) (TVD) 0.00 4 e) 0.00 4 e) Vertical Depth (usft) 0.00 100.00 199.99 299.98 399.96	ACTUAL +N/-S (usft) 0. +N/-S (usft) 0.00 -0.15 -0.74 -1.49 -2.06	(°) 4.57 4.57 00 Tool Name MWD MWD MWD tE/-W (usft) 0.00 0.53 1.73 3.12 4.58	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14 0.73 1.47 2.03	65.74 Description MWD - Standa MWD - Standa MWD - Standa ('/100usft) 0.00 0.63 0.38 0.19 0.02	5 Direction (°) 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00 0.00 18.52 -11.89 -1.56
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00 200.00 300.00 400.00	Sidetrack 1 1.0 To (usft) : 0 3,089.00 1 8,900.00 3 Inclination (°) 0 0.00 0.63 0.92 0.90 0.90 0.74	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor WVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46 123.98 112.09 110.53 105.96	6/27/2014 Phase: pm (TVD) (TVD) 0.00 4 e) e) vertical Depth (usft) 0.00 100.00 199.99 299.98 399.96 499.95	ACTUAL +N/-S (usft) 0. +N/-S (usft) 0.00 -0.15 -0.74 -1.49 -2.06 -2.51	(*) 4.57 4.57 00 Tool Name MWD MWD MWD •+E/-W (usft) 0.00 0.53 1.73 3.12 4.58 5.94	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14 0.73 1.47 2.03 2.47	65.74 Description MWD - Standa MWD - Standa MWD - Standa ('/100usft) 0.00 0.63 0.38 0.19 0.02 0.17	5 Direction (°) 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00 0.00 18.52 -11.89 -1.56 -4.57
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00 200.00 300.00 400.00 500.00 600.00	Sidetrack 1 1.0 To (usft) : 3,089.00 1 8,900.00 3 Inclination (°) 0.00 0.63 0.92 0.90 0.90 0.74 0.55	RF2010 Depth Frc (us Date 7/7/201 Survey (Wellbor WVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46 123.98 112.09 110.53 105.96 117.06	6/27/2014 Phase: pm (TVD) (TVD) 0.00 4 e) 0.00 4 e) Vertical Depth (usft) 0.00 100.00 199.99 299.98 399.96 499.95 599.95	ACTUAL +N/-S (usft) 0. +N/-S (usft) 0.00 -0.15 -0.74 -1.49 -2.06 -2.51 -2.91	(*) 4.57 4.57 00 Tool Name MWD MWD MWD •+E/-W (usft) 0.00 0.53 1.73 3.12 4.58 5.94 6.99	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14 0.73 1.47 2.03 2.47 2.66	65.74 Description MWD - Standa MWD - Standa MWD - Standa ('/100usft) 0.00 0.63 0.38 0.19 0.02 0.17 0.23	5 Direction (°) 18 rd rd rd Rate (°/100usft) 0.00 0.63 0.29 -0.02 0.00 -0.16 -0.19	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00 0.00 18.52 -11.89 -1.56 -4.57 11.10
Audit Notes: Version: Vertical Section: Survey Program From (usft) 100.00 3,134.00 Survey Measured Depth (usft) 0.00 100.00 200.00 300.00 400.00	Sidetrack 1 1.0 To (usft) 3 3,089.00 1 8,900.00 3 Inclination (*) 0.00 0.63 0.92 0.90 0.90 0.74 0.55 0.14	RF2010 Depth Fro (us Date 7/7/201 Survey (Wellbor WVD (OH) Sidetrack 1 (Side Azimuth (°) 0.00 105.46 123.98 112.09 110.53 105.96	6/27/2014 Phase: pm (TVD) (TVD) 0.00 4 e) e) vertical Depth (usft) 0.00 100.00 199.99 299.98 399.96 499.95	ACTUAL +N/-S (usft) 0. +N/-S (usft) 0.00 -0.15 -0.74 -1.49 -2.06 -2.51	(*) 4.57 4.57 00 Tool Name MWD MWD MWD •+E/-W (usft) 0.00 0.53 1.73 3.12 4.58 5.94	Tie On Depth: +E/-W (usft) 0.00 Vertical Section (usft) 0.00 0.14 0.73 1.47 2.03 2.47	65.74 Description MWD - Standa MWD - Standa MWD - Standa ('/100usft) 0.00 0.63 0.38 0.19 0.02 0.17	5 Direction (°) 18 18 18 18 18 18 18 18 18 18	52,020 3,089.00 0.36 Turn Rate (*/100usft) 0.00 0.00 18.52 -11.89 -1.56 -4.57



Company:	Unit Petroleum	Local Co-ordinate Reference:	Well Haw 22 #1H
Project:	Reno County, Kansas [NAD 83]	TVD Reference:	14' KB @ 1756.00usft (UDI 331)
Site:	Section 22 T25S-R10W	MD Reference:	14' KB @ 1756.00usft (UDI 331)
Well:	Haw 22 #1H	North Reference:	Grid
Wellbore:	Sidetrack 1	Survey Calculation Method:	Minimum Curvature
Design:	Sidetrack 1	Database:	EDM 5000.1 Single User Db

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
1,000.00	0.09	292.34	999.94	2.20	9.45	2.25	0.40	-0.27	140.40
1,100.00	0.09	175.03	1,099.94	-2.30 -2.34	8.45 8.38	2.29	0.40 0.15	-0.27	-112.43 -117.31
1,200.00	0.12	189.22	1,199.94	-2.52	8.37	2.46	0.05	0.04	14.19
1,300.00	0.12	103.22	1,299.94	-2.64	8.46	2.59	0.16	0.00	-86.00
1,400.00	0.23	206.53	1,399.94	-2.85	8.47	2.79	0.28	0.11	103.31
1,453.00	0.22	199.12	1,452.94	-3.04	8.39	2.98	0.06	-0.02	-13.98
1,566.00	0.20	259.80	1,565.94	-3.28	8.12	3.23	0.19	-0.02	53.70
1,661.00	1.20	83.90	1,660.93	-3.20	8.95	3.14	1.47	1.05	-185.16
1,755.00	3.60	69.80	1,754.85	-2.08	12.70	2.00	2.61	2.55	-15.00
1,850.00	5.70	71.80	1,849.53	0.43	19.98	-0.55	2.22	2.21	2.11
1,946.00	7.70	68.20	1,944.87	4.30	30.48	-4.50	2.13	2.08	-3.75
2,041.00	7.60	65.60	2,039.02	9.26	42.11	-9.53	0.38	-0.11	-2.74
2,137.00	7.70	66.20	2,134.17	14.48	53.78	-14.82	0.13	0.10	0.63
2,232.00	7.70	65.40	2,228.31	19.70	65.39	-20.11	0.11	0.00	-0.84
2,328.00	7.70	65.20	2,323.45	25.07	77.07	-25.56	0.03	0.00	-0.21
2,424.00	7.40	65.00	2,418.61	30.38	88.52	-30.94	0.31	-0.31	-0.21
2,424.00	7.40	65.70	2,418.01	35.55	99.79	-36.18	0.23	0.21	0.74
2,614.00	7.60	65.70	2,606.97	40.72	111.24	-41.42	0.23	0.21	0.00
2,709.00	7.90	69.40	2,000.97	40.72	123.07	-41.42	0.61	0.00	3.89
2,709.00	7.90	68.50	2,701.10	50.15	134.88	-40.38	0.54	-0.53	-0.95
2,001.00	1.10	00.00	2,700.20	00.10	101.00	00.00	0.04	0.00	0.00
2,898.00	8.00	70.60	2,888.41	54.54	146.68	-55,46	0.70	0.64	2.23
2,992.00	7.60	69.70	2,981.54	58.87	158.68	-59.86	0.44	-0.43	-0.96
3,089.00	7.50	70.20	3,077.70	63.24	170.65	-64.31	0.12	-0.10	0.52
3,134.00	7.30	70.50	3,122.32	65.19	176.11	-66.29	0.45	-0.44	0.67
3,165.00	8.00	73.00	3,153.04	66.47	180.03	-67.60	2.50	2.26	8.06
3,197.00	9.80	80.20	3,184.66	67.59	184.84	-68.75	6.60	5.63	22.50
3,228.00	12.00	89.60	3,215.10	68.06	190.67	-69.26	9.10	7.10	30.32
3,259.00	13.90	100.10	3,245.31	67.43	197.56	-68.67	9.73	6.13	33.87
3,291.00	14,90	111.80	3,276.32	65.23	205.16	-66.52	9,60	3,13	36,56
3,323.00	16.20	121.70	3,307.15	61.35	212.78	-62.69	9.22	4.06	30.94
3,355.00	16.80	131.90	3,337.84	55.92	220.02	-57.30	9.23	1.88	31.88
3,387.00	16.40	142.90	3,368.51	49.22	226.19	-50.64	9.89	-1.25	34.38
3,418.00	16.70	152.70	3,398.23	41.77	230.87	-43.22	9.05	0.97	31.61
3,450.00	17.90	160.50	3,428.79	33.05	234.63	-34.53	8.15	3.75	24.38
3,482.00	20.30	167.10	3,459.03	23.00	237.51	-24.49	10.08	7.50	20.63
3,513.00	23.20	173.00	3,487.82	11.70	239.45	-13.20	11.70	9.35	19.03
3,545.00	26.60	177.10	3,516.85	-1.72	240.58	0.21	11.91	10.63	12.81
3,577.00	30,40	178.40	3,544.96	-16.97	240.38	15,46	12.03	11.88	4.06
3,608.00	34.30	178.40	3,571.15	-33.55	241.64	32.03	12.58	12.58	0.00
3,640.00	38.20	178.50	3,596.95	-52.46	242.15	50.94	12.19	12.19	0.31
2 672 00	44.00	179.00	2 6 2 4 5 7	72.00	242.64	74 07	0.44	0.00	1.05
3,672.00	41.20	178.90	3,621.57	-72.90	242.61	71.37	9.41	9.38	1.25
3,704.00	43.80	179.30	3,645.16	-94.51	242.95	92.98	8.17	8.13	1.25
 3,735.00	45.20	180.00	3,667.27	-116.24	243.08	114.71	4.79	4.52	2.26



Company:	Unit Petroleum	Local Co-ordinate Reference:	Well Haw 22 #1H	
Project:	Reno County, Kansas [NAD 83]	TVD Reference:	14' KB @ 1756.00usft (UDI 331)	
Site:	Section 22 T25S-R10W	MD Reference:	14' KB @ 1756.00usft (UDI 331)	
Well:	Haw 22 #1H	North Reference:	Grid	
Wellbore:	Sidetrack 1	Survey Calculation Method:	Minimum Curvature	
Design:	Sidetrack 1	Database:	EDM 5000.1 Single User Db	

Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
3,767.00	48.10	180.20	3,689.23	-139.50	243.04	137.97	9.07	9.06	0.63
3,798.00	51.00	179.90	3,709.34	-163.09	243.02	161.56	9.38	9.35	-0.97
3,830.00	53.80	180.10	3,728.86	-188.44	243.02	186.91	8.76	8.75	0.63
3,846.00	54.60	180.20	3,738.22	-201.42	242.98	199.89	5.03	5.00	0.63
3,862.00	54.80	180.30	3,747.47	-214.48	242.92	212.95	1.35	1.25	0.63
3,894.00	55.10	179.80	3,765.85	-240.67	242.90	239.14	1.59	0.94	-1.56
3,925.00	55.30	179.90	3,783.54	-266.13	242.97	264.60	0.70	0.65	0.32
3,957.00	55.60	179.80	3,801.69	-292.49	243.04	290.95	0.97	0.94	-0.31
3,989.00	56.00	179.30	3,819.67	-318.95	243.25	317.42	1.80	1.25	-1.56
4,021.00	57.30	179.60	3,837.26	-345.68	243.50	344.14	4.14	4.06	0.94
4,052.00	61.00	180.40	3,853.16	-372.29	243.50	370.75	12.14	11.94	2.58
4,084.00	65.10	181.40	3,867.66	-400.80	243.05	399.27	13.11	12.81	3.13
4,116.00	69.30	181.70	3,880.06	-430.29	242.25	428.76	13.15	13,13	0,94
4,147.00	72.00	181.50	3,890.33	-459.52	241.43	457.99	8.73	8.71	-0.65
4,179.00	74.60	180.60	3,899.52	-490.16	240.87	488.64	8.56	8.13	-2.81
4,210.00	77.50	180.40	3,906.99	-520.24	240.61	518.72	9.38	9.35	-0.65
4,242.00	80.30	181.00	3,913.15	-551.64	240.22	550.12	8.94	8.75	1.88
4,273.00	82.80	180.80	3,917.71	-582.30	239.74	580.78	8.09	8.06	-0.65
4,282.00	83.40	181.40	3,918.79	-591.23	239.57	589.71	9.39	6.67	6.67
4,356.00	87.10	181.40	3,924.92	-664.94	237.77	663.43	5.00	5.00	0.00
4,418.00	88.10	181.30	3,927.51	-726.87	236.31	725.37	1.62	1.61	-0.16
4,480.00	88.80	180.70	3,929.19	-788.84	235.23	787.34	1.49	1.13	-0.97
4,541.00	89.50	180.30	3,930.10	-849.83	234.70	848.33	1.32	1.15	-0.66
4,604.00	90.50	180.50	3,930.10	-912.82	234.26	911.33	1.62	1.59	0.32
4,667.00	91.40	180.20	3,929.05	-975.81	233.87	974.32	1.51	1.43	-0.48
4,728.00	90.50	179.50	3,928.04	-1,036.80	234.03	1,035.31	1.87	-1.48	-1.15
4,791.00	89.90	179.00	3,927.82	-1,099.80	234.86	1,098.30	1.24	-0.95	-0.79
4,853.00	90.20	179.20	3,927.77	-1,161.79	235.83	1,160.29	0.58	0.48	0.32
4,915.00	89.20	179.30	3,928.09	-1,223.78	236.64	1,222.27	1.62	-1.61	0.16
4,978.00	89.80	178.90	3,928.64	-1,286.77	237.63	1,285.25	1.14	0.95	-0.63
5,041.00	90.80	179.50	3,928.31	-1,349.76	238.51	1,348.24	1.85	1.59	0.95
5,102.00	88.80	180.00	3,928.52	-1,410.76	238.78	1,409.23	3.38	-3.28	0.82
5,164.00	89.50	179.50	3,929.44	-1,472,75	239.05	1,471.22	1.39	1.13	-0.81
5,226.00	89.80	179.30	3,929.82	-1,534.75	239.70	1,533.21	0.58	0.48	-0.32
5,287.00	90.10	179.40	3,929.88	-1,595.74	240.39	1,594.20	0.52	0.49	0.16
5,349.00	90.30	179.00	3,929.66	-1,657.74	241.25	1,656.19	0.72	0.32	-0.65
5,410.00	90.90	178.50	3,929.02	-1,718.72	242.58	1,717.16	1.28	0.98	-0.82
5,472.00	89.10	179.10	3,929.02	-1,780.70	243.88	1,779.13	3.06	-2.90	0.97
5,533.00	88.90	179.20	3,930.08	-1,841.69	244.79	1,840.11	0.37	-0.33	0.16
5,594.00	88.80	178.20	3,931.31	-1,902.66	246.17	1,901.07	1.65	-0.16	-1.64
5,655.00	88.90	178.10	3,932.53	-1,963.61	248.14	1,962.02	0.23	0.16	-0.16
5,717.00	88.70	177.90	3,933.83	-2,025.56	250.30	2,023.95	0.46	-0.32	-0.32
5,778.00	89.80	178.20	3,934.63	-2,086.52	252.38	2,084.89	1.87	1.80	0.49



Company:	Unit Petroleum	Local Co-ordinate Reference:	Well Haw 22 #1H
Project:	Reno County, Kansas [NAD 83]	TVD Reference:	14' KB @ 1756.00usft (UDI 331)
Site:	Section 22 T25S-R10W	MD Reference:	14' KB @ 1756.00usft (UDI 331)
Well:	Haw 22 #1H	North Reference:	Grid
Wellbore:	Sidetrack 1	Survey Calculation Method:	Minimum Curvature
Design:	Sidetrack 1	Database:	EDM 5000.1 Single User Db

Survey

Measure Depth (usft)	d Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
5,840	.00 89.80	177.40	3,934.85	-2,148.47	254,76	2,146.83	1.29	0.00	-1.29
5,902	.00 90.50	176.40	3,934.68	-2,210.38	258.11	2,208.72	1.97	1.13	-1.61
5,963	00 91.70	176.40	3,933.51	-2,271.25	261.94	2,269.56	1.97	1.97	0.00
6,025	00 90.20	176.10	3,932.49	-2,333.11	266.00	2,331.39	2.47	-2.42	-0.48
6,086.		175.80	3,932.22	-2,393.95	270.30	2,392.21	0.52	0.16	-0.49
6,148.		175.60	3,932.16	-2,455.78	274.95	2,454.00	0.87	-0.81	-0.32
6,209.		175.00	3,932.48	-2,516.57	279.95	2,514.76	1.04	-0.33	-0.98
6,272.		175.00	3,933.31	-2,579.33	285.44	2,577.48	1.11	-1.11	0.00
6,334.	00 89.00	175.10	3,934.44	-2,641.08	290.79	2,639.21	0.23	0.16	0.16
6,395.		174.30	3,935.62	-2,701.81	296.42	2,699.90	1.35	-0.33	-1.31
6,457.		173.90	3,936.97	-2,763.47	302.79	2,761.51	0.66	-0.16	-0.65
6,518.		173.70	3,938.09	-2,824.10	309.38	2,822.10	0.88	0.82	-0.33
6,582.		174.00	3,938.64	-2,887.73	316.24	2,885.69	1.05	0.94	0.47
6,646.	00 90.00	173.80	3,938.76	-2,951.37	323.04	2,949.28	0.44	0.31	-0.31
6,708.	00 90.10	173.40	3,938.70	-3,012.98	329.95	3,010.85	0.67	0.16	-0.65
6,770.	00 89.20	173.70	3,939.08	-3,074.59	336.91	3,072.41	1.53	-1.45	0.48
6,833.		174.50	3,940.07	-3,137.24	343.39	3,135.03	1.31	-0.32	1.27
6,896.		173.80	3,941.28	-3,199.90	349.81	3,197.64	1.16	-0.32	-1.11
6,959.	00 88.80	174.90	3,942.60	-3,262.58	356.01	3,260.28	1.75	0.00	1.75
7,023.	00 89.80	175.20	3,943.38	-3,326.34	361.53	3,324.00	1.63	1.56	0.47
7,087.	90.00	175.30	3,943.49	-3,390.12	366.83	3,387.75	0.35	0.31	0.16
7,150.		174.30	3,943.33	-3,452.86	372.54	3,450.45	1.66	0.48	-1.59
7,214.		174.20	3,942.71	-3,516.53	378.95	3,514.08	0.80	0.78	-0.16
7,277.0	0 91.10	173.80	3,941.67	-3,579.18	385.54	3,576.69	0.79	0.48	-0.63
7,340.0		173.20	3,940.62	-3,641.77	392.67	3,639.23	1.06	-0.48	-0.95
7,404.0		172.60	3,939.84	-3,705.27	400.58	3,702.68	0.99	-0.31	-0.94
7,468.0		172.00	3,939.56	-3,768.69	409.15	3,766.05	1.44	-1.09	-0.94
7,531.0		172.20	3,939.62	-3,831.09	417.81	3,828.39	0.35	0.16	0.32
7,594.0	90.30	171.80	3,939.45	-3,893.48	426.58	3,890.72	0.79	0.48	-0.63
7,656.0		171.50	3,939.02	-3,954.82	435.58	3,952.01	0.58	0.32	-0.48
7,719.0		171.30	3,938.09	-4,017.11	445.00	4,014.23	1.16	1.11	-0.32
7,783.0		171.20	3,937.08	-4,080.35	454.74	4,077.42	0.95	-0.94	-0.16
7,846.0		170.80	3,936.37 3,936.47	-4,142.57	464.59	4,139.57	0.65	0.16	-0.63
7,908.0	0 89.10	171.10	3,930.47	-4,203.80	474.34	4,200.74	2.63	-2.58	0.48
7,971.0		170.50	3,937.24	-4,265.98	484.42	4,262.86	1.14	0.63	-0.95
8,034.0		170.10	3,937.24	-4,328.08	495.03	4,324.89	1.71	1.59	-0.63
8,096.0		169.80	3,937.19	-4,389.13	505.85	4,385.87	1.53	-1.45	-0.48
8,159.0 8,223.0		169.70 169.10	3,937.63 3,938.19	-4,451.12 -4,514.03	517.06 528.83	4,447.79 4,510.62	0.16 0.99	0.00 -0.31	-0.16 -0.94
8,286.0		168.90	3,938.74	-4,575.87	540.85	4,572.38	0.45	0.32	-0.32
8,349.0		168.70	3,938.96	-4,637.67	553.09	4,634.10	0.71	0.63	-0.32
8,412.0 8,475.0		168.40 167.80	3,938.96 3,939.29	-4,699.41 -4,761.06	565.60 578.59	4,695.77 4,757.33	0.48 1.35	0.00 -0.95	-0.48 -0.95
8,539.0		166.80	3,939.29 3,940.52	-4,823.48	578.59	4,757.55	2.21	-0.95	-1.56
0,009.0	00,40	100.00	0,040.02	-7,020.40	592.00	-,018.00	2.21	-1.00	-1,00



Company:	Unit Petroleum	Local Co-ordinate Reference:	Well Haw 22 #1H
Project:	Reno County, Kansas [NAD 83]	TVD Reference:	14' KB @ 1756.00usft (UDI 331)
Site:	Section 22 T25S-R10W	MD Reference:	14' KB @ 1756.00usft (UDI 331)
Well:	Haw 22 #1H	North Reference:	Grid
Wellbore:	Sidetrack 1	Survey Calculation Method:	Minimum Curvature
Design:	Sidetrack 1	Database:	EDM 5000.1 Single User Db

Survey

Measured Depth I	nclination	Azimuth	Vertical Depth	+N/-S	+E/-W	Vertical Section	Dogleg Rate	Build Rate	Turn Rate
(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
8,603.00	88.00	166.60	3,942.53	-4,885.73	607.37	4,881.82	0.70	-0.63	-0.31
8,667.00	87.10	166.30	3,945.26	-4,947.89	622.35	4,943.89	1.48	-1.41	-0.47
8,730.00	87.00	166.20	3,948.51	-5,009.01	637.30	5,004.90	0.22	-0.16	-0.16
8,740.07	87.06	166.18	3,949.03	-5,018.77	639.71	5,014.65	0.66	0.65	-0.16
Haw 22 1H PBH	IL (6.27)								
8,792.00	87.40	166.10	3,951.53	-5,069.13	652.13	5,064.94	0.66	0.65	-0.16
8,855.00	89.00	167.00	3,953.51	-5,130.37	666.77	5,126.08	2.91	2.54	1.43
Last MWD Surv	ey								
8,900.00	89.00	167.00	3,954,30	-5,174,21	676.90	5,169.86	0.00	0.00	0.00

Measured	Vertical	Local Coo	rdinates	
Depth	Depth	+N/-S	+E/-W	
(usft)	(usft)	(usft)	(usft)	Comment
8,855.00	3,953.51	-5,130.37	666.77	Last MWD Survey
8,900.00	3,954.30	-5,174.21	676.90	Projection to TD

Checked By:

Approved By:

Date: