

Correction

WATER WELL RECORD

Form WWC-5

Division of Water Resources App. No.

1 LOCATION OF WATER WELL: County: <u>Ottawa</u>	Fraction <u>SW 1/4, SE 1/4 SW 1/4 SW 1/4</u> <u>1/4 SW 1/4 SE 1/4 SW 1/4</u>	Section Number <u>21</u>	Township No. T <u>10</u> S	Range Number R <u>3</u> <input type="checkbox"/> E <input checked="" type="checkbox"/> W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here <input type="checkbox"/> <u>HWY 81</u> <u>Minneapolis, KS 67467</u>		Global Positioning System (GPS) information: Latitude: <u>39.161</u> (in decimal degrees) Longitude: <u>-97.663</u> (in decimal degrees) Elevation: <u>1316.74</u> Datum: <input checked="" type="checkbox"/> WGS 84, <input type="checkbox"/> NAD 83, <input type="checkbox"/> NAD 27 Collection Method: <input type="checkbox"/> GPS unit (Make/Model:) <input type="checkbox"/> Digital Map/Photo, <input type="checkbox"/> Topographic Map, <input type="checkbox"/> Land Survey Est. Accuracy: <input type="checkbox"/> <3 m, <input type="checkbox"/> 3-5 m, <input checked="" type="checkbox"/> 5-15 m, <input type="checkbox"/> >15 m		
2 WATER WELL OWNER: <u>USACE</u> RR#, Street Address, Box #: <u>HWY 81</u> City, State, ZIP Code : <u>Minneapolis, KS 67467</u>				

3 LOCATE WELL WITH AN "X" IN SECTION BOX: N <table border="1" style="width: 100%; text-align: center; border-collapse: collapse;"><tr><td style="width: 25%;">NW</td><td style="width: 25%;">NE</td></tr><tr><td>SW</td><td>SE</td></tr></table> S -----1 mile-----	NW	NE	SW	SE	4 DEPTH OF COMPLETED WELL <u>18' 23.2</u> ft. Depth(s) Groundwater Encountered (1) <u>N/A</u> ft. (2)..... ft. (3)..... ft. WELL'S STATIC WATER LEVEL <u>15.79</u> ft. below land surface measured on mo/day/yr. <u>08/25/15</u> Pump test data: Well water was.....ft. after..... hours pumping..... gpm EST. YIELD.....gpm. Well water was.....ft. after..... hours pumping..... gpm Bore Hole Diameter <u>2.756</u> in. to <u>18' 23.2</u> ft. andin. toft. WELL WATER TO BE USED AS: <input type="checkbox"/> Public water supply <input type="checkbox"/> Geothermal <input type="checkbox"/> Injection well <input type="checkbox"/> Domestic <input type="checkbox"/> Feedlot <input type="checkbox"/> Oil field water supply <input type="checkbox"/> Dewatering <input type="checkbox"/> Other (Specify below) <input type="checkbox"/> Irrigation <input type="checkbox"/> Industrial <input type="checkbox"/> Domestic-lawn & garden <input checked="" type="checkbox"/> Monitoring well <u>GMW-1216</u> Was a chemical/bacteriological sample submitted to Department? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No If yes, mo/day/yr sample was submitted..... Water well disinfected? <input type="checkbox"/> Yes <input type="checkbox"/> No
NW	NE				
SW	SE				

5 TYPE OF CASING USED: Steel PVC Other

CASING JOINTS: Glued Clamped Welded Threaded
Casing diameter 2 in. to 10.13 ft., Diameter in. to ft., Diameter in. to ft.
Casing height above land surface 0 in., Weightlbs./ft., Wall thickness or gauge No. Sch.40

TYPE OF SCREEN OR PERFORATION MATERIAL:
 Steel Stainless Steel PVC Other (Specify)
 Brass Galvanized Steel None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
 Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)
 Louvered shutter Key punched Wire wrapped Saw cut Other (specify)

SCREEN-PERFORATED INTERVALS: From 10' 13 ft. to 18' 23.2 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

GRAVEL PACK INTERVALS: From 8' 12 ft. to 22' 23.2 ft., From ft. to ft.
From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other High Solids Bent. Grout

Grout Intervals: From 1 ft. to 12 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:
 Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)
 Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well
 Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well Former Atlas Missile Site

Direction from well Former UST on Site Distance from well within 250 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	3'	Top Soil	23'	27'	<u>Bore Hole Natural Collapse prior to placement of well materials.</u>
3'	8'	Clay/Silt			
8'	18' 14'	Clayey Sand/Silt			
18' 16'	22'	Sand			
14'	16'	<u>Sandy Clay</u>			RECEIVED
22'	27'	<u>Clay</u>			
0	1'	8" FM			<u>OCT 01 2025</u>
		w/2'x2'x1' Concrete Pad			<u>DIVISION OF WATER</u>

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 08/06/2015 and this record is true to the best of my knowledge and belief.
Kansas Water Well Contractor's License No. 903 This Water Well Record was completed on (mo/day/year) 7/16/15
under the business name of ROBERTS ENV. DRILLING, INC. by (signature) Tom Roberts

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at <http://www.kdheks.gov/waterwell/index.html>.