

ROLAN DOUGHTIE, JR. 030000

Division of Water
Resources App. No.

☒ Original Record ☐ Correction ☐ Change in Well Use

Well ID

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction NW ¼ SE ¼ SE ¼ SW ¼		Section Number 31		Township Number T 26 S		Range Number R 3 ☐ E ☒ W															
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: ☐ Business: Horsch Homes Construction Address: P.O. Box 284 Address: City: Andale State: KS ZIP: 67001 30510 W 29th St N 30530 W 29th St N Garden Plain, KS 67050 Garden Plain, KS 67050																							
3 LOCATE WELL WITH "X" IN SECTION BOX: N <table border="1" style="width:100px; height:100px; text-align: center; margin: 10px auto;"> <tr><td> </td><td> </td><td> </td></tr> <tr><td>-- NW --</td><td>-- NE --</td><td> </td></tr> <tr><td>W</td><td> </td><td>E</td></tr> <tr><td>-- SW --</td><td>-- SE --</td><td> </td></tr> <tr><td> </td><td>X</td><td> </td></tr> <tr><td> </td><td>S</td><td> </td></tr> </table> -----1 mile-----					-- NW --	-- NE --		W		E	-- SW --	-- SE --			X			S		4 DEPTH OF COMPLETED WELL: 90 ft. Depth(s) Groundwater Encountered: 1) 45 ft. 2) ft. 3) ft., or 4) ☐ Dry Well WELL'S STATIC WATER LEVEL: 50 ft. ☒ below land surface, measured on (mo-day-yr) 08/09/2021 ☐ above land surface, measured on (mo-day-yr) / / Pump test data: Well water was ft. after hours pumping gpm Well water was ft. after hours pumping gpm Estimated Yield: 11 gpm Bore Hole Diameter: 10.5 in. to 90 ft. and in. to ft.		5 Latitude: 37.735980 (decimal degrees) Longitude: -97.691260 (decimal degrees) Datum: ☒ WGS 84 ☐ NAD 83 ☐ NAD 27 Source for Latitude/Longitude: ☐ GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No) ☐ Land Survey ☐ Topographic Map ☐ Online Mapper:	
-- NW --	-- NE --																						
W		E																					
-- SW --	-- SE --																						
	X																						
	S																						
7 WELL WATER TO BE USED AS: 1. Domestic: ☒ Household ☐ Lawn & Garden ☐ Livestock 2. ☐ Irrigation 3. ☐ Feedlot 4. ☐ Industrial 5. ☐ Public Water Supply: well ID 6. ☐ Dewatering: how many wells? 7. ☐ Aquifer Recharge: well ID 8. ☐ Monitoring: well ID 9. Environmental Remediation: well ID ☐ Air Sparge ☐ Soil Vapor Extraction ☐ Recovery ☐ Injection 10. ☐ Oil Field Water Supply: lease 11. Test Hole: well ID ☐ Cased ☐ Uncased ☐ Geotechnical 12. Geothermal: how many bores? a) Closed Loop ☐ Horizontal ☐ Vertical b) Open Loop ☐ Surface Discharge ☐ Inj. of Water 13. ☐ Other (specify):		Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted: Water well disinfected? ☒ Yes ☐ No																					
8 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other CASING JOINTS: ☒ Glued ☐ Clamped ☐ Welded ☐ Threaded Casing diameter 5 in. to 90 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 16 in. Weight lbs./ft. Wall thickness or gauge No. SDR-26 TYPE OF SCREEN OR PERFORATION MATERIAL: ☐ Steel ☐ Stainless Steel ☒ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)		SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous Slot ☒ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify) ☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☐ Saw Cut ☐ None (Open Hole)																					
SCREEN-PERFORATED INTERVALS: From 20 ft. to 90 ft., From ft. to ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 22 ft. to 90 ft., From ft. to ft., From ft. to ft., From ft. to ft.		9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other Grout Intervals: From 3 ft. to 22 ft., From ft. to ft., From ft. to ft., From ft. to ft. Nearest source of possible contamination: No potential source of contamination within 200 ft. ☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage ☐ Sewer Lines ☐ Cess Pool ☒ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well ☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well ☐ Other (Specify) Direction from well? West Distance from well? 200 ft.																					
10 FROM TO LITHOLOGIC LOG		FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS																					
0	2	Top Soil																					
2	20	Tan Clay																					
20	40	Tan Clay/Shale																					
40	45	Gray Clay/Shale																					
45	50	Red Clay/Red Shale																					
50	90	Red Shale																					
		Notes:																					
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo-day-year) 08/09/2021 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 884 This Water Well Record was completed on (mo-day-year) 03/30/2022 under the business name of Weninger Drilling, LLC Send one copy to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212																							