

☒ Original Record ☐ Correction ☐ Change in Well Use

Well ID

7 WELL WATER TO BE USED AS:

1. Domestic:	5. ☐ Public Water Supply: well ID	10. ☐ Oil Field Water Supply: lease
☒ Household	6. ☐ Dewatering: how many wells?	11. Test Hole: well ID
☐ Lawn & Garden	7. ☐ Aquifer Recharge: well ID	☐ Cased ☐ Uncased ☐ Geotechnical
☐ Livestock	8. ☐ Monitoring: well ID	12. Geothermal: how many bores?
2. ☐ Irrigation	9. Environmental Remediation: well ID	a) Closed Loop ☐ Horizontal ☐ Vertical
3. ☐ Feedlot	☐ Air Sparge ☐ Soil Vapor Extraction	b) Open Loop ☐ Surface Discharge ☐ Inj. of Water
4. ☐ Industrial	☐ Recovery ☐ Injection	13. ☐ Other (specify):

Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted:

8 TYPE OF CASING USED: ☐ Steel ☒ PVC ☐ Other CASING JOINTS: ☒ Glued ☐ Clamped ☐ Welded ☐ Threaded
Casing diameter 5" in. to 15.0 ft. Diameter in. to ft. Diameter in. to ft.
Casing height above land surface 3' in. Weight 56.40 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL:

- ☐ Steel ☐ Stainless Steel ☐ Fiberglass ☒ PVC
☐ Brass ☐ Galvanized Steel ☐ Concrete tile ☐ None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- ☐ Continuous Slot ☒ Mill Slot ☐ Gauze Wrapped ☐ Torch Cut ☐ Drilled Holes ☐ Other (Specify)
☐ Louvered Shutter ☐ Key Punched ☐ Wire Wrapped ☒ Saw Cut ☐ None (Open Hole)

SCREEN-PERFORATED INTERVALS: From 150 ft. to 170 ft., From ft. to ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 35 ft. to 170 ft., From ft. to ft., From ft. to ft.

9 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☒ Bentonite ☐ Other
Grout Intervals: From 5 ft. to 35 ft., From ft. to ft., From ft. to ft.

Nearest source of possible contamination:

- ☐ Septic Tank ☐ Lateral Lines ☐ Pit Privy ☐ Livestock Pens ☐ Insecticide Storage
☐ Sewer Lines ☐ Cess Pool ☐ Sewage Lagoon ☐ Fuel Storage ☐ Abandoned Water Well
☐ Watertight Sewer Lines ☐ Seepage Pit ☐ Feedyard ☐ Fertilizer Storage ☐ Oil Well/Gas Well
☐ Other (Specify)

Direction from well? Distance from well? ft.

10 FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHO. LOG (cont.) or PLUGGING INTERVALS
0	1	Top soil	115	126	Limestone (water)
1	11	Limestone	126	135	Brown shale
11	13	Yellow shale	135	138	Limestone
13	15	Limestone	138	142	Brown shale
15	49	Brown shale	142	150	Limestone
49	56	Grey shale	150	170	Grey shale
56	81	Tan shale	Notes:		
81	94	Limestone			
94	115	Grey shale			

Notes:

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, ☐ reconstructed, or ☐ plugged under my jurisdiction and was completed on (mo-day-year) 8/3/2026 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo-day-year) 8/11/2026 under the business name of Haldema Wick Drilling Craig H. Wick C.W.D.P.R.

Mail 1 white copy along with a fee of \$5.00 for each constructed well to: Kansas Department of Health and Environment, Bureau of Water, GWTS Section

1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524.

Visit us at <http://www.kdheks.gov/waterwell/index.html>

KSA 82a-1212

Revised 1/20/2015