


1 LOCATION OF WATER WELL:	Fraction LOT 8	Section Number	Township Number	Range Number
County: WABAUNSEE	SW 1/4 SW 1/4 SE 1/4	17	T 10 S	R 10 EX

Distance and direction from nearest town or city street address of well if located within city?

1.25 MILES SOUTH & 1 MILE WEST

2 WATER WELL OWNER: LOUIS H. WEIXELMANN	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : RT. 1 BOX 9	Application Number: 38248
City, State, ZIP Code : WAMEGO KS 66547	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 18 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 18 ft. below land surface measured on mo/day/yr 5-7-96
	Pump test data: Well water was 27 ft. after 1 hours pumping 750 gpm
	Est. Yield 1500 gpm: Well water was 35 ft. after 2 hours pumping 1250 gpm
	Bore Hole Diameter 32 in. to 65 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	5 Public water supply 8 Air conditioning 11 Injection well
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No XX

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 16 in. to 45 ft., Dia			11 Other (specify)
Casing height above land surface 12 in., weight			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	
1 Steel	3 Stainless steel	6 Concrete tile	9 ABS
2 Brass	4 Galvanized steel		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 45 ft. to 65 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 18 ft. to 65 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals:	From 0 ft. to 18 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? SOUTH			13 Insecticide storage	
			How many feet? 75	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	BROWN TOP SOIL			
2	9	BROWN SANDY SILT			
9	16	FINE BROWN SAND			
16	23	SMALL-MEDIUM BROWN GRAVEL			
23	25	MEDIUM GREY GRAVEL & GREY CLAY			
25	28	MEDIUM GREY GRAVEL			
28	29	MEDIUM-GREY GRAVEL & GREY CLAY			
29	34	MEDIUM-LARGE GREY GRAVEL & COBBLES			
34	36	TREE OR WOOD			
36	65	LARGE GREEN GRAVEL			
	65	LARGE ROCKS , STOPPED			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-7-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 323 This Water Well Record was completed on (mo/day/yr) 5-9-96 under the business name of HOOBLER DRILLING CO. by (signature) Daniel Hoobler
