


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 NE 1/4 Section Number 5 Township Number T 10 S R 10 Range Number EW
 County: Pottawatomie
 Distance and direction from nearest town or city street address of well if located within city? (Wamego - Elementary Parking lot)
Approximately 200' SW of Kaw Valley and Say road intersection

2 WATER WELL OWNER: US Army Corp of Engineers Ltrn: Saqik Khan-PM
 RR#, St. Address, Box #: 601 Eggb 12th St, RM 810 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Kansas City, MO 64106 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 73.3' ELEVATION: 1059.45' AMSL - ground surface
 Depth(s) Groundwater Encountered: 1 56.0' ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 49.89' ft. below land surface measured on mo/day/yr 8/30/04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter in. to ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface Flush mount in., weight lbs./ft. Wall thickness or gauge No.
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 63.3' ft. to 73.3' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 57.0' ft. to 73.5' ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite Seal 4 Other
 Grout Intervals: From 0' ft. to 54.0' ft., From 54.0' ft. to 57.0' ft., From ft. to ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3.0	Topsoil/Fill			
3.0	14.9	Sandy Clay - Reddish Brown			
14.9	30.0	Sand - Coarse, Orange-Brown			
30.0	41.0	Silt - Tan, dense			
41.0	57.0	Silt - Tan, Sand and Clay lenses, Peat lenses			
57.0	73.5	Sand - Medium to fine w/ coarse zones, saturated below 56.0' b. Drive barrel refusal at 73.5' (possible sand stone).			

RECEIVED
 AUG 26 2004
 BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8/30/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. Federal Government This Water Well Record was completed on (mo/day/yr) 8/30/04 under the business name of US Army Corp of Engineers by (signature) [Signature] - Geologist