


1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 SE 1/4 Section Number 2 Township Number T 10 S Range Number R 10 E 3
 County: Pottawatomie

Distance and direction from nearest town or city street address of well if located within city?
2 1/2 mi. E, 1/4 mi. N. of Wamego

2 WATER WELL OWNER: Dick Chrest Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: R.R. 1 Application Number:
 City, State, ZIP Code: Wamego, KS 66547

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 49 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 18 ft. 2. 18 ft. 3. 7-6-81 ft.
 WELL'S STATIC WATER LEVEL: 18 ft. below land surface measured on mo/day/yr 7-6-81
 Pump test data: Well water was 25 ft. after 24 hours pumping 12 gpm
 Est. Yield 25 gpm: Well water was 25 ft. after 24 hours pumping 12 gpm
 Bore Hole Diameter: 8 1/2 in. to 49 ft., and 49 in. to 49 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Fish (bait) ponds
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped No
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded No
 7 Fiberglass Threaded No
 Blank casing diameter 5 in. to 29 ft., Dia. 5 in. to 29 ft., Dia. 5 in. to 29 ft.
 Casing height above land surface 18 in., weight 214 lbs./ft. Wall thickness or gauge No. 214
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 11 Other (specify) 11
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) 10
 SCREEN-PERFORATED INTERVALS: From 29 ft. to 49 ft., From 29 ft. to 49 ft., From 29 ft. to 49 ft.
 GRAVEL PACK INTERVALS: From 13 ft. to 49 ft., From 13 ft. to 49 ft., From 13 ft. to 49 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other 2
 Grout Intervals: From 3 ft. to 13 ft., From 13 ft. to 49 ft., From 13 ft. to 49 ft., From 13 ft. to 49 ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage Abandoned Sand point
 Direction from well? North How many feet? 15

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	12'	Silt			
12'	18'	Fine Sand			
18'	29'	Sand - up to 1/8" dia. multi-colored			
29'	35'	Fine Sand			
35'	49'	Sand - up to 1/8" dia. Multi-colored			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-8-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 405 This Water Well Record was completed on (mo/day/yr) 8-2-81 under the business name of Haworth Drilling by (signature) Walter Haworth

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY T 10 R 10 BW SEC. 2