


1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 County: POTTAWATOMIE SW 1/4 SW 1/4 NE 1/4 6 T 10 S R 10 E/W

Distance and direction from nearest town or city street address of well if located within city?
1 1/2 west of Wamego

2 WATER WELL OWNER: Jay Hildreth
 RR#, St. Address, Box # : 15955 Cedar Meadows Rd. Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Wamego, KS 66547 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL... 115' ft. ELEVATION:
 Depth(s) Groundwater Encountered 1. 50' ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL .. 41' ft. below land surface measured on mo/day/yr .. 12-15-93
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield ... 15 ... gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter .. 12" in. to ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No.....X...; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued .. X .. Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5" in. to .. 0-46 ft., Dia ... 5" in. to .. 51-71 ft., Dia ... 5" in. to .. 75-94 .. 100-115
 Casing height above land surface .. 24" in., weight ... 2.82 lbs./ft. Wall thickness or gauge No. ... 258
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 46 ft. to ... 51 ft., From ... 71 ft. to ... 75 ft.
 From 94 ft. to ... 100 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 24 ft. to ... 115 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to .. 24 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? east How many feet? 210'

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|---|------|----|--------------------|
| 0 | 2 | Top Soil | | | |
| 2 | 31 | Clay-Brown-Silty | | | |
| 31 | 41 | Fine Sand-Brown | | | |
| 41 | 50 | Fine Sand-Coarse Sand-Brown | | | |
| 50 | 58 | Clay-Brown | | | |
| 58 | 65 | Clay-Blue | | | |
| 65 | 70 | Clay-Brown | | | |
| 70 | 74 | Fine Silt-Brown | | | |
| 74 | 94 | Clay-Blue | | | |
| 94 | 97 | Fine Sand-Coarse Sand-Med Gravel-Boulders-Clay-Blue | | | |
| 97 | 115 | Shale-Grey | | | |
| 115 | | Limestone-Grey | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) ... 12-15-93 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. ... 182 This Water Well Record was completed on (mo/day/yr) .. 1-13-94 under the business name of STRADER DRILLING CO., INC. by (signature) Dalviksen

OFFICE USE ONLY
T
R
E/W
SEC.
1/4
1/4
1/4