_									
PCMW-4D			***	WO 5					
WATER WELL RECORD 1 LOCATION OF WATER WELL:			Form W	WC-5		er Resources App. No			
	CATION OF WA nty: Pottawotom		Fraction 1/4 NE 1/4 NE	1/4 NW 1/4	Section Number	Township No. T 10 S	Range Number R 10 ☑E □	OL/	
Street/Rural Address of Well Location;								··	
from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information: Latitude:39.201483				
			-		Longitude: -96.3	Longitude: -96.304937 (in decimal degrees)			
Lincoln St. & Ash St. between 4th & 5th St. War				.	Elevation:		••••	-,	
2 WATER WELL OWNER: KDHE / RER					Datum: WGS	84, 🗌 NAD 83, 🗌	NAD 27		
		INDI IL.			Collection Method:				
	, Street Address,	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	V Jackson St., Suite	410	GPS unit (Ma	ke/Model:		.)	
City	, State, ZIP Code	· Topeka.	Ks. 66612-1367		☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey Est. Accuracy: ☐ <3 m, ☐ 3-5 m, ☐ 5-15 m, ☐ >15 m				
3 LOC	ATE WELL	I				3-13 III, 1 - 13 III			
1	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 58 ft.								
SEC	SECTION BOX: Depth(s) Groundwater Encountered (1).35								
							کراهی/ارکراریay/yr.		
		oing gpn							
	WNE				ping gpm	1			
W Bore Hole Diameter 8.25 in. to									
WELL WATER TO BE USED AS:								۸.	
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below) Irrigation Industrial Domestic-lawn & garden ✓ Monitoring well								,	
			bacteriological sample				********************	•	
	S		day/yr sample was sub			100 23 710			
ļ	l mile	Water well disin	fected? Yes	No					
5 TYPE OF CASING USED: Steel PVC Other									
CASING JOINTS: Glued Clamped Welded Threaded									
Casing diameter .2 in. to .48 ft., Diameter ft., Diameter in. to ft.,									
Casing height above land surface. 0 in., Weight									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
☐ Steel ☐ Stainless Steel									
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE: ☐ Continuous slot									
☐ Continuous slot ☑ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☐ Wire wrapped ☐ Saw cut ☐ Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From									
From									
6 GROUT MATERIAL: Neat cement Coment grout Bentonite Other									
Grout Intervals: From . 0									
What is the nearest source of possible contamination:									
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☐ Other (specify below) ☐ Sewer lines ☐ Cesspool ☐ Sewage lagoon ☐ Fuel storage ☐ Abandoned water well									
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well									
Direction from well									
FROM	TO	LITHOLOG		FROM			GGING INTERVAL		
0	7.5 silty cla	ay (cl), dark brow	n, soft,	40		overy, caving san			
	moist								
7.5		n),dark brown,							
	stiff, m	oist							

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks and check the correct answers. Send one copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.

Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at