


1 LOCATION OF WATER WELL: Fraction SW 1/4 NW 1/4 NW 1/4 Section Number 3 Township Number T 10 S Range Number R 11 E
 County: Pottawatomie

Distance and direction from nearest town or city street address of well if located within city?
1/4 mi. W, 1/2 mi. S, & 1/4 mi. E. of Belvue, Ks.

2 WATER WELL OWNER: Kansas Power & Light Co. Board of Agriculture, Division of Water Resources
 RR#, St. Address, Box #: 818 Kansas Ave. Application Number: -
 City, State, ZIP Code: Topeka, Ks. 66601

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION: 945 ±
 Depth(s) Groundwater Encountered 1. 4.5 ft. 2. 4.5 ft. 3. 4.5 ft.
 WELL'S STATIC WATER LEVEL 4.5 ft. below land surface measured on mo/day/yr 5/26/82
 Pump test data: Well water was max 1,100 gpm: Well water was 30 in. to 65 ft. and 65 in. to 65 ft.
 Est. Yield 1,100 gpm: Well water was 30 in. to 65 ft. and 65 in. to 65 ft.
 Bore Hole Diameter: 30 in. to 65 ft. and 65 in. to 65 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded
 Blank casing diameter 16 in. to 25 ft. Dia. 25 in. to 25 ft. Dia. 25 in. to 25 ft. Dia. 25 in. to 25 ft.
 Casing height above land surface 60 in. weight 24.25 lbs./ft. Wall thickness or gauge No. 188
 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 25 ft. to 65 ft. From 25 ft. to 65 ft. From 25 ft. to 65 ft. From 25 ft. to 65 ft.
 GRAVEL PACK INTERVALS: From 5 ft. to 65 ft. From 5 ft. to 65 ft. From 5 ft. to 65 ft. From 5 ft. to 65 ft.

6 GROUT MATERIAL: 1 Neat cement 2 ~~Cement grout~~ 3 Bentonite 4 Other compacted clay fill
 Grout Intervals: From 0 ft. to 5 ft. From 5 ft. to 65 ft. From 5 ft. to 65 ft. From 5 ft. to 65 ft.
 What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? Northwest How many feet? 770 ft.

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	7	fill material			
7	20	coarse gravel			
20	21	gray clay			
21	30	coarse sand and gravel			
30	40	coarse sand, gravel, w/ boulders.			
40	50	gray sand and gravel.			
50	65	yellow sandy gravel.			
65		shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/25/82 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 429 This Water Well Record was completed on (mo/day/yr) 6/29/82 under the business name of Subgrade Construction by (signature) J. H. Umbraugh SEA
 INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

10

R

11

EW

SEC.

3

SW 1/4

NW 1/4

NE 1/4

SE 1/4