WATER WELL RECORD Form WWC-5 Division of Water Resources App. No. 47709	
1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range	
County: Wabaunsee	⊠E □W
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here \square . Global Positioning System (GPS) information: Latitude: (in decim	al deorees)
Longitude: (in decim	al degrees)
Elevation:	,
2 WATER WELL OWNER: Steven Holz RR#, St. Address, Box # 22284 Wells Creek Rd Datum: □ WGS 84, □ NAD 83, □ NAD 27 Collection Method: Collection Method:	
City, State, ZIP Code Belyue, KS 66407)
☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land So	urvey
Est. Accuracy: □ <3 m, □ 3-5 m, □ 5-15 m, □ >15 m	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 95 ft.	
SECTION BOX: Depth(s) Groundwater Encountered (1) ft. (2) ft. (3)	ft.
N WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr	
Pump test data: Well water was ft. after hours pumping	gpm
NW NE EST. YIELD gpm: Well water was ft. after hours pumping	gpm
WELL WATER TO BE USED AS: ☐ Public water supply ☐ Geothermal ☐ Injection well	
Domestic ☐ Feedlot ☐ Oil field water supply ☐ Dewatering ☐ Other (Specify SW SE ☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well	below)
SW SE Ixi Irrigation Industrial Domestic-lawn & garden Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No	
S If yes, mo/day/yr sample was submitted	
1 mile Water Well Disinfected? ⊠ Yes □ No	
5 TYPE OF CASING USED: ☐ Steel ☑ PVC ☐ Other	
CASING JOINTS: Simple Clamped Welded Threaded Casing diameter 16 in. to 75 ft., Diameter in. to ft., Diameter in. to Casing height above land surface 24 in., Weight 16.15 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL:	
Casing height above land surface 24 in Weight 16.15 the /ft Well thickness or gauge No.	ft.
THE ST SCHEET ON TEM ORATION MATERIAL.	.500
☐ Steel ☐ Stainless Steel ☑ PVC ☐ Other (Specify) ☐ Brass ☐ Galvanized Steel ☐ None used (open hole)	
☐ Brass ☐ Galvanized Steel ☐ None used (open hole) SCREEN OR PERFORATION OPENINGS ARE:	
☐ Continuous Slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole)	
□ Louvered shutter □ Key punched □ Wire wrapped □ Saw cut □ Other (specify) SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft. From ft. to	
SCREEN-PERFORATED INTERVALS: From 75 ft. to 95 ft., From ft. to	ft.
GRAVEL PACK INTERVALS: From 20 ft. to 95 ft., From ft. to ft. to	ft.
From ft. to ft., From ft. to	ft.
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals From 0 ff to 20 ft From ft to ft From ft to ft From ft fro	
Grout Intervals From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to	ft.
Septic tank	cify below)
Sewer lines	eny octow)
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well None Direction from well ☐ Distance from well	
FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING IN 6 Surface	NTERVALS
6 34 Clay	
34 38 Clay & sand strks	
38 59 Med sand & gravel 59 74 River mud & fine sand strks	
74 96 Med sand & course gravel	
96 Shale black	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or □ plu	igged
under my jurisdiction and was completed on (mo/day/year) 11/17/11 and this record is true to the best of my knowledge	ge and belief.
Kansas Water Well Contractor's License No. 554 . This Water Well Record was completed on (mo/day/year) 11/2	2/11
lunder the business name of Woofter Pitmin & Wall Inc.	
under the business name of Woofter Pump & Well Inc. by (signature) INSTRUCTIONS: Please fill in blanks and check the correct answers. Send three copies (white, blue, pink) to kansas Department of Health and Environm Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWN	ant Duran of