CORRECTION(S) TO WATER WE (to rectify lacking or incorre	
Location listed as:	Location changed to:
Section-Township-Range: 16-105-11E	16-105-UE
Fraction (¼ ¼ ¼): 5E NW NW	16-105-11E NE NE ≤W
Other changes: Initial statements: Pottamatomic. (County
Changed to: Wa baunsee Count	γ
Comments:	

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

verification method: Legal description, position on plat map, and Belvine 1:24,000 topo map (buildings shown)

initials: BPL date: 8/30/2005

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas State Dept. Of Health (Water Well Contractors) Forbes-Bldg. 740 Topeka, Kansas 66620

1 Location of well: Pottaulatomie Township name Fraction SEN	Nh	1 .	n number	16 T.10S Range number Range number
Distance and direction from nearest town or city:	3 Owner	r of well:	Sch	leif, Ernest
Street address of well location if in city:	Addr	ess:	Rura	l Route
Locate with "X" in section below: N		_		e kansas 4 Well depth: 4732 ft. Date of completion 12/5/75 Well diameter 10 in.
				5 🖾 Cable tool 🗌 Rotary 📗 Driven 🗎 Dug 📗 Hollow rod 🔲 Jetted 🔲 Bored 🔲 Reverse rotary
w E				6 Use: Domestic Public supply Industry Irrigation Air conditioning Commercial Test well
s				7 Casing: Material Steethight: above/below Threaded Welded Wisurface 13 in. Diam. 654 Weight 13 lbs./ft.
1 Mile→				in. to ft. depth Drive shoe? ☐ Yes No in. to ft. depth!
2 Type and color of material		From	То	8 Screen:
Top Soil		0	3	Manufacturer <u>Steel Pipe & Supply</u> Type <u>Steel</u> Dia. <u>6-5/8</u> Slot/gauze thole Stength 7 feet
Black Fine Sand		3	17	Set between _3.2. ft. and _3.9 ft
White Clay With Fine Sand		17	23	Fittings: Gravel pack ី Yes 🗌 No Size range of material 🌲
Yellow CRay With Sand		23	32	9 Static water level: 25 ft. below land surface Date 12/5/75
Sand and Gravel in Yellow Clay		32	40	10 Pumping level below land surfaces: ft. after hrs. pumping g.p.m.
White Shale		40	47	ft. after hrs. pumping g.p.m. Estimated maximum yield g.p.m.
Red Shale		4.7	<u> </u>	11 Water sample submitted:
				12 Well head completion:
·				☐ Pitless adapter ☐ Inches above grade ☐ I3 Well grouted? ☐ Yes ☐ No
				Neat cement Bentonite Depth: From 3 ft. to 13ft.
				14 Nearest source of possible contamination: ft
				15 Pump: Not installed
				Manufacturer's name Pumpco Model number HP 1/3 Volts 230
		ļ	ļ	Length of drop pipe 40 ft. capacity 7 g.m.p.
				Submersible
(use a second sheet if needed)				☐ Jet ☐ Reciprocating ☐ Certrifugal ☐ Other
16 Remarks: elevation Slab to be installed by Cu	uston	ner		17 Water well contractor's certification: This well was drilled under my jurisdiction and this
Topography:				sport is true to the best of my knowledge and belief.
Hill Slope				Business name Address No.
Upland Valley				Signed Signed Authorized representative
Forward the white, blue and pink copies to the Kansas State Dept. Of Health.				Form WWC-5