

County: Pottawatomie Fraction: NW NW NENE Sec. 2 T 10 S R 11 E

CORRECTION(S) TO WATER WELL COMPLETION RECORD (WWC-5) - to rectify lacking or incorrect information

Owner: Westar Energy

If corrected, location was listed as:

Location changed to:

Section-Township-Range: none listed

sec 2 T10S R11E

Fraction (1/4 1/4 1/4): none listed

NW NW NENE

Other changes: Initial statements: no quarter calls or STR listed
well use not listed

Changed to: sec 2 T10S R11E, NWNW NENE, irrigation

Comments: _____

Verification method: Mapper site with lat/long coordinates, talked with driller

Initials: MS Date: 08-28-2018

Submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Avenue, Lawrence, KS 66047-3724
 Kansas Dept. of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367

WATER WELL RECORD Form WWC-5

Division of Water Resources App. No.

Well ID Well 13

Original Record Correction Change in Well Use

1 LOCATION OF WATER WELL: County: Pottawatomie Well 13 Fraction 1/4 1/4 1/4 1/4 Section Number Township Number T S Range Number R E W

2 WELL OWNER: Last Name: Business: Westar Energy Address: 818 South Kansas Avenue City: Topeka State: KS ZIP: 66612 Street or Rural Address where well is located

3 LOCATE WELL WITH 'X' IN SECTION BOX: 4 DEPTH OF COMPLETED WELL: 42.5 ft. 5 Latitude: N39.21664 Longitude: W096.15101

7 WELL WATER TO BE USED AS: 1. Domestic: 2. Irrigation 3. Feedlot 4. Industrial 5. Public Water Supply 6. Dewatering 7. Aquifer Recharge 8. Monitoring 9. Environmental Remediation 10. Oil Field Water Supply 11. Test Hole 12. Geothermal 13. Other

Was a chemical/bacteriological sample submitted to KDHE? Water well disinfected?

8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter 18 in. to 42.5 ft. Diameter in. to ft. Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From 22.5 ft. to 42.5 ft. GRAVEL PACK INTERVALS: From 20 ft. to 42.5 ft.

9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other Grout Intervals: From 11.6 ft. to 0 ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Cess Pool Sewage Lagoon Fuel Storage Abandoned Water Well Watertight Sewer Lines Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) None Direction from well? Distance from well? ft.

10 FROM TO LITHOLOGIC LOG FROM TO LITHO. LOG (cont.) or PLUGGING INTERVALS 42.5' 11.6' Washed River Rock 11.6' 0' Cement Grout

11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year) 11/14/2016 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 631. This Water Well Record was completed on (mo-day-year) 11/30/2016 under the business name of Alexander Pump & Services, Inc. Signature