USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

DDA

V.X

Kansas Department of Health and Environment-Division of Environment (Woter well Contractors) Topeka, Kansas 66620

| 1 1 1 | County | Ctr. of | SE N | 15 | Section | number | Township number | Range number | | |
|--|--------------------------------------|---------------|------|----------|-------------------|--|---|-------------------------|---------------|--|
| 1. Locotion of well: | Wabaunsee Wabaunsee 1/4 # 1/4 | | | ₩/0 | | т 1 0 s | R 11 | E/W | | |
| | ection from nearest town or city: 31 | Schoemann | | | | | | | | |
| St. Marys, Ks. on U.S.24, 2mi.So., 1½mi. West Street address of well location if in city: & ½ mi. North. City, stot | | | | | Λ. Λ. #1 | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | | | Marys. Ks. 66536 6. Bore hole dia. 30 in. Completion date 8-30-77 | | | |
| | | | | | | | Well depth 36 ft. | Completion date 2 | <u></u> | |
| -NWNE | | | | | Ì | | 7 Cable tool Rotary | Driven Dug | | |
| E CARACTE E CARA | | | | | | | Hollow rod Jetted Bored X_ Reverse rotary | | | |
| | | | | | >> _ | | 8. Use: Domestic Public supply Industry | | | |
| | | | | | | 2 | Lawn Oil field water Other | | | |
| | | | | | | | 9. Casing: Material stee | | | |
| <u> </u> | | | | | | | Threoded WeldedX Surface18 ⁿ in. | | | |
| S I———— 1 Mile ———————————————————————————————————— | | | | | | RMPPVCWeightlbs./ft. Dia. 16n. to 16 ft. depth Wall Thickness: inches or | | | | |
| 5. Type and color of material | | | | | From | То | Diain. to ft. dept | h gage No. 029 | ines or | |
| | | | | | | | 10. Screen: Manufacturer's no | ome Free-Flo | | |
| Fine brown sand | | | | | 0 | 2 | W. A. Brown Ent | erprises Dig. 16" | | |
| 0-64 | | | | | | | Slot gauze 1/4x4 | Length20 ° | | |
| Soft gray silty clay | | | | | _2_ | 10 | Set between 16 | ft. and <u>36</u> | ft. | |
| Fine to med. gray gravel & gray clay | | | | | 10 | 12 | Gravel pack? YES Size ran | | -1/4" | |
| Med. gray gravel | | | | | 40 | 17 | 11. Static water level: | mo., | /day/yr. | |
| | | | | \neg | 12 | 17 | ft. below land surf | | 27 | |
| Med. to large gray gravel | | | | _ | 17 | 20 | 12. Pumping level below land 17 ft. after 1 hr | | 00.0.m. | |
| Fine to med. gray gravel | | | | | 20 | 24 | 25 ft. after3 hrs. pumping 1200 g.p.m. | | | |
| | | | | | | | Estimated maximum yield 1500 g.p.m. | | | |
| Med. gray gravel | | | | \dashv | 24 | 29 | 13. Water sample submitted: mo./day/yr. Yes X No Date | | | |
| Med. to large gray gravel | | | | | 29 | 36 | 14. Well head completion: | | | |
| Gray shale-stopped. | | | | | 36 | | Pitless adapter | Inches above g | grade | |
| | | | | |)0 | | 15. Well grouted? | _ Bentonite _X C | | |
| | | | | _ | | | Depth: From 0 ft. to1 | O ft. | | |
| | | | | | | | 16. Nearest source of possible | contamination: | . ' * | |
| | | | | | | | ft. 80 Direction Well disinfected upon complete | | x No. | |
| | | | | _ | | \vdash | | X Not installed | | |
| | | | | | | | Manufacturer's name | | | |
| | | | | | | | | HP Volt ft. capacity | | |
| | | | | \neg | | | Type: | . 11. capacity | g.p.m. | |
| - | | | | \dashv | | | Submersible | Turbine | . 1 | |
| | (Use a second sho | et if needed) | | | | | Jet Centrifugal | Reciproc | coring S | |
| 18. Elevation: 19. Remarks: Woods not install number | | | | | | | 20. Water well contractor's ce | rtification: | 1,10 | |
| 942 Delay in filing report due to delay in | | | | | | | This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Hoobler Drilling Co. 323 | | | |
| | | | | | | in | | | | |
| Hill obtaining legal description. | | | | | | | Business name St. Marris Vs. 66526 | | | |
| Slope | | | | | | Address Storiarys, | | 26 22 5 | | |
| Y Voliev | | | | | | | Signed — Althorized repre | Date 9 | | |