USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Konsas Department of Health and Environment-Division of Environment (Woter well Contractors)

	LC	<u>.</u>			Topeka, Kansas 66620
County	Fraction	Fraction Section number		number	Township number Range number
1. Location of well: WALAUNSER	5W 5W 1/45W	1/4	\ \ <u>\ \</u>	2	T 10 (S) R 11 (EW)
•	- 1	3 0	ner of wal	i. 10	C. ClawitteR
2. Distance and direction from neorest town or city: Street address of well location if in city: OF WAMEGO 3. Owner of well: R.R. or street: City, stote, zip code:				c. CHWITTER	
Street address of well location if in city: $ ho f$	WAMEGO			code: F	RI Belove Ks 66407
4. Locate with "X" in section below:	Sketch map:				6. Bore hole dia. — in. Completion date —
N N					Well depth 100 ft. 11-10-78
	5410				7 Cable tool Look Rotary Driven Dug Hollow rod Jetted Bored Reverse rotary
	<i>/</i> \ \ .	1			
E E	/ \}	200			8. Use:Domestic Public supply Industry Irrigation Air conditioning Stock
	Wark a))			LawnOil field water Other
SW SE	House	١.			9. Casing: Material PVC Height: (boye or below
		1			Threaded Surface in.
S 1 Add -		X 4	eil		RMP PVC91 Weight 2.55 lbs./ft.
5 Tracerd color of material			Τ.	T -	Dia 5 in. to 100 ft. depth Wall Thickness: inches or Diain. to ft. depth gage No. 1274
5. Type and color of material			From	То	10. Screen: Manufacturer's name
					YUMPCO MPI
TOP SOIL			10	4	Type Dia. 5
Clay BROWN			4	18	(Sof) gauze 1020 Length 40 Set between 20 ft. and 60 ft.
Clay, Blown					ft. andft.
LimesTONE, 9Rey	1004.4.000.00		18	19	Gravel pack? Size range of material 1030×1060
Limestowe, gley Shale, gley Limestone, g	Pau		19	100	11. Static water level: mo./day/yr.
SHATE, GRAY TIMESTONE, 4	key		177	100	
,					12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m.
					ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m.
			 	-	Estimated maximum yield 10 qp# g.p.m.
					13. Water sample submitted: mo./day/yr.
					Yes No Date
					14. Well head completion: C4P
					Pitless adapter
					15. Well grouted? Bentonite Concrete
					Depth: From ft. to/_5 ft.
					16. Nearest source of possible contamination:
					ft. 200 Direction Type SepTIC
					Well disinfected upon completion? YesNo
					17. Pump:Not installed
					Model number HP Volts
					Length of drop pipe ft. capacityg.p.m.
					Type:
					Submersible Turbine Reciprocating
(Use	a second sheet if needed)				Centrifugal Other
18. Elevation: 19. Remarks: ,					20. Water well contractor's certification:
1067					This well was drilled under my jurisdiction and this report
Topography: OWNER TO IN	KTAIL SLAL				is true to the best of my knowledge and belief. STRAGER DRIG C3 182
Hill	574/1 5/Ab				STRADER DRIA (3 182) Business name License No.
Slope					Address RT1 HolTon, 145
Upland					Signed Wale askren Date 11-13-18
Valley					Authorized representative
Forward the white, blue and pink copies to the D	Pengriment of Health and Environment				Form WWC-5

Forward the white, blue and pink copies to the Department of Health and Environment

BR=1049

₹ = 1049