

WATER WELL RECORD Form WWC-5 KSA 82a-1212					
1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: POTT.		N. C. X OF W. 1 / 4 N.W. 1 / 4	7	T 10 S	R 12 E/ WX
Distance and direction from nearest town or city street address of well if located within city? TWO MILES WEST OF ST. MARYS KS.					
2 WATER WELL OWNER: PESSEMIER CO. C/O CHRISTIAN ROYER RR#, St. Address, Box # : BOX 206 Board of Agriculture, Division of Water Resources City, State, ZIP Code : ST. MARYS KS 66536 Application Number: 3752 & 28009					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N +---+ NW --- NE ---+ W E +---+ SW --- SE ---+ S		4 DEPTH OF COMPLETION WELL... 63 ft. ELEVATION: Depth(s) Groundwater Encountered 1... 17 ft. 2... ft. 3... ft. WELL'S STATIC WATER LEVEL .17 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was N.A. ft. after N.A. hours pumping N.A. gpm Bore Hole Diameter .in. to .ft., and .in. to .ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No XX; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded XX Blank casing diameter .in. to .ft., Dia .in. to .ft., Dia .in. to .ft. Casing height above land surface .36 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel X.X. 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot N.A. 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes SCREEN-PERFORATED INTERVALS: From N.A. ft. to .ft., From .ft. to .ft. GRAVEL PACK INTERVALS: From .63 ft. to .17 ft., From .ft. to .ft. From .ft. to .ft., From .ft. to .ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From .ft. to .ft., From .ft. to .ft., From .ft. to .ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? 15 IRRIGATION WELL.....					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
			64	17	CHLORINATED UD 1, SAND
			17	4	COMPACTED SURFACE SOILS
			4	3	3/8 GRANULAR BENTONITE
			3	0	CASING CUT OFF & WELL COVERED OVER
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-10-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 323 This Water Well Record was completed on (mo/day/year) 5-2-97 under the business name of HOOBLER DRILLING CO. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					