

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

Blank box for application number

1 LOCATION OF WATER WELL: County: Wabaunsee Fraction: NE 1/4 SW 1/4 SE 1/4 Section Number: 34 Township Number: T 100 Range Number: R 12 EW

Distance and direction from nearest town or city street address of well if located within city? Blacktop + 3 1/2 From Maple Hill to 2 Northway North West on Gravel (Turkey Creek Rd)

Global Positioning Systems (decimal degrees, min. of 4 digits) Latitude: Longitude: Elevation: Datum: Data Collection Method:

2 WATER WELL OWNER: Bill Schneider RR#, St. Address, Box #: 16524 Turkey Creek City, State, ZIP Code: Maple Hill, KS 66507

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: N W E S

4 DEPTH OF COMPLETED WELL: 5.0 ft. Depth(s) Groundwater Encountered (1) 2.4 ft. (2) ft. (3) ft. WELL'S STATIC WATER LEVEL: 2.4 ft. below land surface measured on mo/day/yr. Pump test data: Well water was... ft. after... hours pumping... gpm Est. Yield: 50 gpm: Well water was... ft. after... hours pumping... gpm

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded Threaded 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below)

Blank casing diameter: 5 in. to 30 ft., Diameter: 30 in. to 50 ft., Diameter: 50 in. to 50 ft., Diameter: 50 in. to 50 ft. Casing height above land surface: 20 in., Weight: 56.40 lbs./ft. Wall thickness or guage No.:

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 9 ABS 11 Other (Specify) 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 10/1000 5 Guarded wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From: 30 ft. to 50 ft., From: 30 ft. to 50 ft., From: 30 ft. to 50 ft., From: 30 ft. to 50 ft.

GRAVEL PACK INTERVALS: From: 25 ft. to 50 ft., From: 25 ft. to 50 ft., From: 25 ft. to 50 ft., From: 25 ft. to 50 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From: 5 ft. to 25 ft., From: 5 ft. to 25 ft., From: 5 ft. to 25 ft., From: 5 ft. to 25 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify below) 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 14 Abandoned water well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer Storage 15 Oil well/gas well Old but hole

Direction from well? 110' south How many feet? 110'

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Log entries: 0-1 Top Soil, 1-24 Brown Clay, 24-28 Fine Sand, 28-50 Course Sand (Water)

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/5/2009 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 451 This Water Well Record was completed on (mo/day/year) 5/8/2009 under the business name of Wabaunsee Well Drilling by (signature) Craig L. Campbell

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline & circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdhe.state.ks.us/geo/waterwells.