(DRL, 7/1/2013)

\sim	(L) (1/1/2/5)					3,752	
WATER WEL		Form W	WC-5		r Resources App. No		
1 LOCATION	OF WATER WELL:	Fraction	17 NIM 17	Section Number 7	Township No. T 10 S	Range Number R 12	
County: Pottawa tomie SE 1/4 SW 1/4 NW 1/4 NW 1/4 Street/Rural Address of Well Location; if unknown, distance & direction					<u> </u>		
from nearest town or intersection: If at owner's address, check here				Global Positioning System (GPS) information: Latitude: .39,19874(in decimal degrees)			
From Belvue 2 E. 1 S. 1 E. 1/2 S. 1/4 N. in field				Longitude: 096.12639 (in decimal degrees)			
Prom Belvu	8 Z E. 1 3. 1 E. 1/2 3. 1/	4 N. III lielu		Elevation: .955			
				<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, [] NAD 27			
2 WATER WELL OWNER: Pessemier Co. c/o Cristian Rover				Collection Method:			
RR#, Street Address, Box #: P.O. Box 206				☐ GPS unit (Make/Model: Garmin Csx ☐ Digital Map/Photo, Topographic Map, ☐ Land Survey			
City, State, ZIP Code : Saint MArv's, Kansas 66536				Est. Accuracy: \square <3 m, \square 3-5 m, \square 5-15 m, \square >15 m			
3 LOCATE WELL							
	WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 7.1						
SECTION BO	Depth(s) Groundwater Encountered (1)						
N	WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr. 2-4-2013						
	Pump test data: Well water wasft. after hours pumping gpm						
NW N							
W	E Bore Hole Diameterin. toft., andin. toft.						
	WELL WATER TO BE USED AS: Public water supply Geothermal Injection well						
SW S	Domestic Feedlot Oil field water supply Dewatering Other (Specify below)						
	✓ Irrigation						
S If yes, mo/day/yr sample was submitted							
Water well disinfected?							
5 TYPE OF CASING USED: Steel PVC Other							
Casing diameter .16							
Casing height above land surface. 24 in., Weight SCH 40 lbs./ft., Wall thickness or gauge No500							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
☐ Steel							
☐ Brass ☐ Galvanized Steel ☐ None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
☐ Continuous slot ☐ Mill slot ☐ Gauze wrapped ☐ Torch cut ☐ Drilled holes ☐ None (open hole) ☐ Louvered shutter ☐ Key punched ☑ Wire wrapped ☑ Saw cut ☐ Other (specify)							
SCREEN-PERFORATED INTERVALS: From 41							
SCREEN-PERFORATED INTERVALS: From 41 ft. to 6.1 ft., From 61 ft. to 71 ft. to ft. From ft. to ft., From ft. to ft.							
GRAV	EL PACK INTERVALS:	From. 71	t. to20	ft From	ft. 1	to ft.	
		From 1					
6 GROUT MATERIAL: ☐ Neat cement ☐ Cement grout ☑ Bentonite ☐ Other							
Grout Intervals:	From .20 ft. to		f	t. to ft.,	From	. ft. toft.	
What is the nearest source of possible contamination:							
☐ Septic tank ☐ Lateral lines ☐ Pit privy ☐ Livestock pens ☐ Insecticide storage ☑ Other (specify below)							
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well None							
	n well			rom well			
FROM TO	LITHOLOG		FROM			GGING INTERVALS	
0 3	Sandy top						
3 7	Brown clay-silty	**************************************	T-				
7 40	Medium to fine sand						
40 71	Fine to medium sand w	vith streaks					
	of rock						
		- Andrew Miles - Andrew Miles - Andrew Miles		,			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed, reconstructed, or plugged							
under my jurisdiction and was completed on (mo/day/year) .2-4-20.13 and this record is true to the best of my knowledge and belief.							
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 2-19-2013							
INSTRUCTIONS: Use ty pewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies							
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 666 12-1367.							
Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at							
http://www.kdheks.gov/waterwell/index.html							
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy							