

54

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

DBB

WATER WELL RECORD
KSA 82a-1201-1215

prob. in direction

Kansas Department of Health and Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

NWC-NW-SE

1. Location of well: County WABAUWSEE Fraction NE SW Section number 33 Township number T 10 S R 12 E/W

2. Distance and direction from nearest town or city 3 N - 2 W 3. Owner of well: Ed Hutley
Street address of well location if in city: OF MAPLE HILL RFD
City, state, zip code: MAPLE HILL, KS 66507

4. Locate with "X" in section below: Sketch map:

6. Bore hole dia. 10 in. Completion date 4-29-76
Well depth 57 ft.

7. Cable tool Rotary Driven Dug
 Hollow rod Jetted Bored Reverse rotary

8. Use: Domestic Public supply Industry
 Irrigation Air conditioning Stock
 Lawn Oil field water Other

9. Casing: Material PVC Height: Above or below
Threaded Welded Surface 24 in.
RMP PVC 9L Weight 258 lbs./ft.
Dia. 5 in. to 57 ft. depth Wall Thickness: inches or
Dia. in. to ft. depth gage No. 1258

5. Type and color of material	From	To
<u>TOP SOIL</u>	<u>0</u>	<u>6</u>
<u>BROWN CLAY</u>	<u>6</u>	<u>35</u>
<u>FINE SAND</u>	<u>35</u>	<u>40</u>
<u>COURSE SAND - GRAVEL</u>	<u>40</u>	<u>48</u>
<u>BLUE SHALE</u>	<u>48</u>	<u>57</u>

10. Screen: Manufacturer's name PUMPCO
Type PVC Dia. 5"
Slot/gauge .025 Length 10
Set between 40 ft. and 50 ft.
Gravel pack? Size range of material 0.30x.080

11. Static water level: 35 ft. below land surface Date 4-29-76 mo./day/yr.

12. Pumping level below land surfaces: AIR TEST
 ft. after hrs. pumping g.p.m.
 ft. after hrs. pumping g.p.m.
Estimated maximum yield 30 g.p.m.

13. Water sample submitted: mo./day/yr.
Yes No Date

14. Well head completion: CAPPED
 Pitless adapter 29 inches above grade

15. Well grouted?
With: Neat cement Bentonite Concrete
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination: 100 ft. Direction NW Type SEPTIC
Well disinfected upon completion? Yes No

17. Pump: installed
Manufacturer's name JACH221
Model number 554B-32 HP 1/2 Volts 230
Length of drop pipe 50 ft. capacity 10 g.p.m.
Type:
 Submersible Turbine
 Jet Reciprocating
 Centrifugal Other

18. Elevation: 978'
Topography: Hill Slope Upland Valley

19. Remarks: OWNER WILL INSTAL SLAB

20. Water well contractor's certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
STRAKER Dslg Co Inc 182
Business name License No.
Address PTI Holton, KS
Signed Dale Ashen Date 4/30/76
Authorized representative

10
120
34
SUSW500
1/4 1/4 1/4

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5