


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>SHANNIC 089</u>		<u>NW 1/4 NW 1/4 NW 1/4</u>	<u>12</u>	T <u>10 S</u>	R <u>12 E</u>
Distance and direction from nearest town or city street address of well if located within city? <u>From ST Marys GO 1 mile North on 63 Highway + 60 1/2 miles West on Jesuit Cemetery on MT Colvary Ad.</u>					
2 WATER WELL OWNER: <u>Robert P. Kaiser</u>		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: <u>601 Birchwood Ct.</u>		Application Number:			
City, State, ZIP Code: <u>ST Marys, Kansas 66536</u>					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: <u>40</u> ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. <u>30</u> ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL <u>12</u> ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield <u>100</u> gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter <u>10</u> in. to <u>40</u> ft. and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS <u>Glued</u> Clamped			
1 Steel 3 RMP (SR)		Welded			
2 PVC 4 ABS		Threaded			
5 Wrought iron 8 Concrete tile					
6 Asbestos-Cement 9 Other (specify below)					
7 Fiberglass					
Blank casing diameter <u>5</u> in. to <u>20</u> ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface <u>3</u> in., weight <u>54.40</u> lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		12 None used (open hole)			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS					
SCREEN OR PERFORATION OPENINGS ARE:		8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot <u>25 1000</u>		9 Drilled holes			
2 Louvered shutter 4 Key punched		10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From <u>20</u> ft. to <u>40</u> ft. From ft. to ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From <u>20</u> ft. to <u>40</u> ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:		4 Other			
1 Neat cement 2 Cement grout 3 Bentonite					
Grout Intervals: From <u>20</u> ft. to <u>20</u> ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines <u>None Close</u>		11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool		12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit		13 Insecticide storage			
7 Pit privy 8 Sewage lagoon					
9 Feedyard					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top Soil			
3	200	Brown Clay			
20	30	Brown Clay + Fine Gravel			
30	34	Gravel (Water)			
34	36	Limstone			
36	40	Grey Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>12/28/94</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>451</u> This Water Well Record was completed on (mo/day/yr) <u>2/5/95</u> under the business name of <u>HALDCMAN WELL DRILLING</u> by (signature) <u>Ray E. Cline</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					