

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Shawnee	NE ¼ SW ¼ SW ¼	5	T 10 S	R 15E E/W

Distance and direction from nearest town or city street address of well if located within city?
6 1/4 miles north and 2 miles west of Topeka

2 WATER WELL OWNER:	Gil Werner	11-26-07	
RR#, St. Address, Box # :	5619 Sw 14th	*permission to shallow grout*	
City, State, ZIP Code :	Topeka, Ks. 66604	Board of Agriculture, Division of Water Resources Application Number:	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 65 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 10 ft. below land surface measured on mo/day/yr 8-2-07 Pump test data: Well water was ft. after hours pumping gpm Est. Yield 8 gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yrs sample was submitted Water Well Disinfected? Yes X No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to	ft., Dia 24 in. to	ft., Dia	Threaded
Casing height above land surface	in., weight 2.82 lbs./ft.	Wall thickness or gauge No. .258	
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless Steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
			10 Asbestos-Cement
			11 Other (Specify)
			12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Guazed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
		7 Torch cut	11 None (open hole)
		10 Other (specify)	ft.
SCREEN-PERFORATED INTERVALS: From 12 ft. to 32 ft., From ft. to ft.			
GRAVEL PACK INTERVALS: From 1.1 ft. to 6.5 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 11 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? north			13 Insecticide storage	ditch
			How many feet? 60'	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	top soil			
3	12	brown clay			
12	14	clay brown sandy			
14	17	chert grey			
17	23	grey grey shale			
23	30	grey limestone			
30	37	grey shale			
37 37	43	grey limestone			
43	47	grey shale			
47	53	grey limestone			
53	58	grey shale			
58	60	grey limestone			
60	65	grey shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-2-07 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 182 This Water Well Record was completed on (mo/day/yr) 9-27-07 under the business name of Strader Drilling Co., Inc. by (signature) <i>[Signature]</i>
--