WATE	R WELL I	RECORD	Form WWC-	5 Divisi			rces; App. No.		
1 LOCA	ATION OF V	WATER WELL:	Fraction NW 4 SE 4	SW ¼	ction Nu 31	mber	Township Number	Range Number R 16 E	
County: Shawnee NW 4 SE 4 SW 4 31 T 10 S R 16 E Distance and direction from nearest town or city street address of well if Global Positioning System (decimal degrees, min. of 4 digits)									
located within city? 4727 NW Levering Dr. Topeka KS Latitude: NA Longitude: NA									
2WATER WELL OWNER: Wilk									
RR#, St. Address, Box # : 4727 NW Levering Dr.					atum:	NA			
City.	State, ZIP Co	de : Topek	a KS	D	ata Colle	ection M	ethod: legal surve	у	
3 LOC	ATE WELL	S 4 DEPTH O	F COMPLETED WE	LL 180			ft.		
LOCATON									
	H AN "X" IN	Depth(s) Grou	indwater Encountered 1	NA		ft. 2	ft. 3	3 ft.	
	TION BOX:	WELL'S STA	indwater Encountered 1 TIC WATER LEVEL	NA ft. l	elow lar	nd surfac	ce measured on mo	/day/yr	
	N.	Pun	Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm						
i		Est. Yield	gpm: Well wate	er was	ft.	after	hours pum	ping gpm	
		WELL WATE	R TO BE USED AS: :	5 Public wate	r supply	8 A11	conditioning $\downarrow 1$	injection wen	
	N NE	1 Domestic 3	Feed lot 6 Oil field	water supply	•	9 Dewa	itering 1270	ther (Specify below)	
W		E 2 Irrigation	4 Industrial 7 Domesti	ic (lawn & ga	rden) 1	0 Moni	toring well	Geothermal	
SW — SE — Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, r									
								; If yes, mo/day/yrs	
<u> </u>	S	Sample was s	ubmitted		V	Vater W	ell Disinfected? Y	es No X	
Sample was submitted Water Well Disinfected? Yes No X 5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete tile CASING JOINTS: Glued Clamped									
5 TYPE OF CASING USED: 5 Wrought Iron 8 Concrete the CASING JOHN 15. Gladd Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Fusion									
1 81	1 Steel 3 RMP (SR) 6 Asbestos-Cement Other (specify below) Welded Fusion Polyothylene Threaded								
1 Steel 3 RMP (SR) 6 Asbestos-Cement 2 PVC 4 ABS 7 Fiberglass Polyethylene Threaded Blank casing diameter 3/4 in. to 180 ft., Dia in. to ft., Dia in. to ft. Casing height below land surface 4 ft., Weight Ibs./ft. Wall thickness or gauge No. 160 PSI TYPE OF SCREEN OR PERFORATION MATERIAL:									
Blank casing diameter 3/4 in. to 180 II., Dia III. to 1t., Dia III. to 1t.									
Casing height below land surface 4 ft., Weight 108./Tt. Wall thickness of gauge No. 100 FSI									
1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 9 ABS 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR) 10 Asbestos-Cement 12 None used (open hole)									
CODEEN OF DEPEND ATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)									
1 Continuous slot 3 Mill slot 5 Gauze wrapped 7 Torch cut 9 Drilled holes 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 8 Saw Cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From ft. to ft.									
SCREEN	N-PERFORA	TED INTERVAL	S· From	tt. to		ft. Fre	om 11	ι. ιο	
			From	TL. TO		п. гв	OIII I	ι. ιυ	
GRAVEL PACK INTERVALS: From				ft. to		ft. Fr	om f	t. to π	
From ft. to ft. From ft. to								ι. ιο	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Sentonite 4 Other Grout Intervals From 4 ft. to 180 ft. From ft. to ft. From ft. to ft.									
Grout Intervals From 4 ft. to 180 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 13 Insecticide Storage 16 Other (specify									
2 Se	wer lines		ol 8 Sewage lagoon	11 Fuel stor	age		andoned water well	l below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 15 Oil well/ gas well									
Direction	a from well?			How many	feet?				
FROM	TO	LITH	OLOGIC LOG	FROM	TO		PLUGGING IN	ITERVALS	
0		Brown silty clay							
15		Gray silty shale							
45		White limestone				4-180	borings plugged		
55		Black-gray silty	shale		100	Domto	n.i.t.o.		
105		White limestone		4	180	Bento	mie		
115		Black silty shale	AND THE RESERVE OF THE PERSON			-			
120		While limestone Dark gray silty s	hala					Later II	
160 165	165 180	White limestone	mall						
						1			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged									
and this record is trile and was completed on (mo/day/year)									
Kansas Water Well Contractor's License No. 757 . This Water Well Record was completed on (mo/day/year) 1/15/12									
under the business name of Larsen & Associates, Inc. by (signature)									
INSTRUCTIONS: Please fill in blanks or circle the copies to Kansas Department of Neath and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to TER WELL OWNER and retain one for									
Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WIEL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at http://www.kdheks.gov/waterwell.									
July 10001									