LOCATION OF W	ATER WELL:		WELL HECO	no romi	Section N	mbar	Township Nur	mbor.	Pango	Number
		Fraction	8 1 1A /	5			l '• •	$\sim$		
ounty: Leaven	Worth	NW 1/4	NN 1/4	SW	4 2 -	<u>,                                     </u>	T 10	(s)	<u> </u>	2 1 (E)W
tance and direction	n from nearest town o	or city street add	ress of well i	r located with	in city? 2%	E 2	1210 OF 7	TON9A	NOX18	
WATER WELL O	WNER: Tom G	urss								
	0x # : RR 2 B						Board of Ag	riculture. [	Division of W	ater Resource
	TONGAN		001				Application I			
y, State, ZIF Code	70109710	UXIO GIB	000		20					
LOCATE WELL'S AN "X" IN SECTION	LOCATION WITH 4	DEPTH OF CO	MPLETED W	ELL	بخڊft.∣	ELEVAT	ΓΙΟΝ:			
AN A IN SECTIO	N De	epth(s) Groundwa	ater Encounte	red 1	<i>15</i>	ft. 2		ft. 3		
	T i w	ELL'S STATIC V	VATER LEVE	L5	ft. below la	nd surf	ace measured on r	no/dav/vr	10-27	-802
							ter			
NW	NE    _	·~	_					•		
1							ter			
w   1	l Bo	ore Hole Diamete	er	.in. to	<i>.</i>	ft., a	ınd	in.	. to	
"וען	I I W	ELL WATER TO	BE USED A	S: 5 Pul	blic water supp	ly :	8 Air conditioning	11	Injection well	
^	1 1 1	1 Domestic	3 Feedic	t 6 Oil	field water suc	via	9 Dewatering	12	Other (Speci	fv below)
SW	SE	2 Irrigation	4 Industr				0 Observation well			
	<b>!</b>	•								
	l Wa	as a chemical/ba	icteriological s	ample submit	ted to Departm	ent? Ye	sNo.—	; If yes,	mo/day/yr sa	ampie was su
	S mi	tted				Wat	er Well Disinfected	? Yes_	No	
TYPE OF BLANK	CASING USED:		5 Wrought iro	on 8	3 Concrete tile		CASING JOIN	TS: Glued	Cla بيب ال	mped
1 Steel	3 RMP (SR)		6 Asbestos-C	ement 9	Other (specif	v below	<i>'</i> )	Welde	ed	
2 PVC	4 ABS		7 Fiberglass		` .	•		Three	aded	
	r <b></b> in.									
	land surface		n., weight			Hbs./f	t. Wall thickness or	gauge No	0 4. 5. 6.	
PE OF SCREEN	OR PERFORATION M	MATERIAL:			7 PVC_		10 Asbe	stos-ceme	ent	
1 Steel 3 Stainless steel			5 Fiberglass	8 RMP (SR	)	11 Other	11 Other (specify)			
2 Brass	4 Galvanized		6 Concrete til		9 ABS	<b>,</b>		used (op		
									,	
	PRATION OPENINGS			5 Gauzed wra			8 Saw cut		11 None (c	pen noie)
1 Continuous s	lot 3 Mill s	slot	(	6 Wire wrapp	ed		9 Drilled holes			
2 Louvered shu	tter 4 Key j	punched	-	7 Torch cut			10 Other (specify)			
REEN-PERFORA	TED INTERVALS:	From	2	ft to 22		ft. From	n	ft. to	0	
							n			
0041/51 0										
GRAVEL P	ACK INTERVALS:	From	·				n <i></i>			π
		From		ft. to		ft., Fron	n	ft. to	0	ft
GROUT MATERIA	L: 1 Neat cem	nent 2	Cement grou	ıt	3 Bentonite	4 (	Other			
out Intervals: Fr	om <i>Q</i> ft.	to 10	ft From	1	ft. to		ft From		ft. to	
	source of possible cor		,				ock pens		bandoned wa	
	•		7.04	-i			•		il well/Gas w	
1 Septic tank	4 Lateral li		7 Pit p	•			storage			
2 Sewer lines 5 Cess pool			8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)				
3 Watertight se	wer lines 6 Seepage	e pit	9 Feed	lyard	13	Insect	icide storage .			
rection from well?	ΝĒ				H	ow man	y feet? <b>90</b>			
ROM TO		LITHOLOGIC LO	OG	F	ROM TO			ITHOLOG	IC LOG	
0 3	TOP Soil									
	Clay Las					_				
3 12	SANDSTON	1.								
12 17	SANUSTON	1e								
17 30	Shalagrey									
	1									
										<del></del>
	· · · · · · · · · · · · · · · · · · ·									
										<u> </u>
										;
							-			
										111
									<del></del>	
							<u> </u>			
	1									
CONTRACTOR'S	OR LANDOWNER'S	CERTIFICATIO								
npleted on (mo/da	y/year) . <i>I.Q</i> ; 2. 7.	7-82					d is true to the best			belief. Kansa
	r's License No	82					on (mg/day/yr)			
								1		
ET THE DUSINESS N	ame of Strader	Urillir	9 Co.	Lne		(signati			skre	Mara Candin
	typewriter or ball poin									
	s Department of Health	n and Environme	TIE, DIVISION OF	⊏⊓vironment,	⊏⊓vironmental	Geolog	y Section, Topeka, I	<b>13 00020.</b>	Send one to	WAIED WEL
WIED and rotain of	one for your records.									-