

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Leavenworth	SW 1/4 SW 1/4 SE 1/4	13	T 10 S	R 21 E E/W

Distance and direction from nearest town or city street address of well if located within city?

4 1/2 miles North and 2 1/4 miles east of Tonganoxie

2 WATER WELL OWNER: Jim & Sandy Trobridge	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 19263 Green Rd	Application Number:
City, State, ZIP Code : Tonganoxie, Ks. 66086	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 80 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
	WELL'S STATIC WATER LEVEL 2.1 ft. below land surface measured on mo/day/yr 1.0-6-04
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield 35 gpm: Well water was ft. after hours pumping gpm
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No x ; If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes x No	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued x Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC	4 ABS	7 Fiberglass Threaded
Blank casing diameter 5" in. to ft., Dia in. to ft., Dia in. to ft., Dia in. to ft., Dia
Casing height above land surface 24" in., weight 2.82 lbs./ft.	Wall thickness or gauge No. 258		
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel 3 Stainless Steel 5 Fiberglass 7 PVC 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 8 RMP (SR) 11 Other (Specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot 3 Mill slot 5 Guazed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.			
SCREEN-PERFORATED INTERVALS: From 25 ft. to 35 ft., From 65 ft. to 80 ft.			
GRAVEL PACK INTERVALS: From 23 ft. to 80 ft., From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 23 ft., From ft. to ft.				
What is the nearest source of possible contamination:				
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage				
Direction from well? SouthWest		How many feet? 200		

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	top soil			
2	11	clay brown			
11	24	clay brown sandy			
24	32	fine/course sand brown			
32	46	clay brown			
46	65	clay tan grey			
65	68	fine/course sand med pea grey/brown mix			
68	71	limestone grey			
71	74	shale grey			
74	80	limestone grey			

RECEIVED
NOV 22 2004
BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-9-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 182 . This Water Well Record was completed on (mo/day/yr) 11-9-04 under the business name of Strader Drilling Co., Inc. by (signature) <i>Jim Strader</i>	
--	--

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.