

1 LOCATION OF WATER WELL: Fraction NW 1/4 SW 1/4 NW 1/4 Section Number 16 Township Number T 10 S Range Number R 21 (E/W)

Distance and direction from nearest town or city street address of well if located within city?

2 WATER WELL OWNER: Kenneth Criswell
 RR#, St. Address, Box #: 22542 219th Street
 City, State, ZIP Code: Leavenworth, Ks. 66048
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

| | | | |
|---|---|--|---|
| N | | | |
| | | | |
| | X | | |
| W | | | E |
| | | | |
| | | | |
| S | | | |

4 DEPTH OF COMPLETED WELL 120 ft. ELEVATION: 120 ft.
 Depth(s) Groundwater Encountered 1 48 ft. 2 85 ft. 3 ft.
 WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 1.5 gpm Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS:
 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Domestic (lawn & garden) 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below)

Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:
 1 Steel 2 PVC 3 RMP (SR) 4 ABS 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below)
 Blank casing diameter 8 5/8 in. to 50 ft., Dia 5" PVC in. to 120 ft., Dia in. to ft.
 Casing height above land surface in., weight lbs./ft. Wall thickness or guage No. 220 PSI SDR 21
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 2 Brass 3 Stainless Steel 4 Galvanized Steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-Cement 11 Other (Specify) 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Guazed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole)
 SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft., From 120 ft. to 110 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 120 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below)
 Direction from well? How many feet? +150'

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|-----------------------------|------|----|---------------------------|
| 0 | 21 | Clay | 0 | 25 | Bentonite seal on annular |
| 21 | 31 | Sandy clay | | | |
| 31 | 65 | Coarse sand & small pebbles | | | |
| 65 | 85 | Shale | | | |
| 85 | 97 | Sandstone | | | |
| 97 | 120 | Shale | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 6/16/06 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 595 This Water Well Record was completed on (mo/day/yr) 6/25/06 under the business name of Jesse Yeakum Well Drilling by (signature) Jesse Yeakum