		WA	ATER WELL REC	ORD Form	WWC-5	KSA 82a	-1212 IE	D No			
1 LOCATI	ON OF WA		Fraction				ction Numb	er To	wnship Number	Range Numbe	r
County: I			SW 14	NW 1/4	NW 1/4		32	Т	10 s	R 22E E	E/W
			wn or city street a								
		est of B	-								
	WELL OW	.=-	n KKMXXX	Brulja	a						
RR#, St. Ad		DO	239- 178t	_	ı			B	oard of Agriculture	Division of Water Reso	nurces
City, State,					006				oplication Number:		urces
3 1 00 1		TO	nganoxie,	MPLETED W	7511	120	ft FI F				
	SECTION		Donth(a) Croun	dwater Englis	otorod 1		11	# 2	4	3	f+
	N	DOX.	WELL'S STATIO	WATER LEV	FI 33	ft be	low land su	rface measu	red on mo/day/yr	8-19-04	
	1		Pur	np test data:	Well water	was		ft. after	hours	pumping	. gpm
×	, I	NE	Est. Yield	Q gpm:	Well water	was		ft. after	hours	pumping	. gpm
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well										,	
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below 1										
W <del> </del>	T T	E	2 illigation	4 maasiii	iai / D	oniesiic (ia	wii a gaide	10 10101111	oning wen	,	•••••
	1	-					_				
	SW SE   Was a chemical/bacteriological sample submitted to Department? Yes NoX; If yes, mo/day/yrs sa									mo/day/yrs sample was	s sub-
mitted Water Well Disinfected? Yes X											
	S										
5 TYPE C	OF BLANK C	CASING USED:		5 Wrought in		8 Conc				uedx Clamped	
	1 Steel 3 RMP (SR) 6 Asbestos-Ce					9 Other	r (specify below)		Welded		
2 PVC		4 ABS	7 Fiberglass						readed		
										in. to	
	•			in., weigh	t2			lbs./ft. W	•	age No 258	••••••
TYPE OF SCREEN OR PERFORATION MATERIAL:						7 P			10 Asbestos-Cement		
101					Fiberglass		8 RMP (SR) 9 ABS		11 Other (Specify)		•••••
2 Brass 4 Galvanized Steel 6 Concrete tile											
SCREEN OR PERFORATION OPENINGS ARE:						ed wrapped		8 Sav		11 None (open hole	<del>)</del> )
	inuous slot		Mill slot		vrapped cut		9 Drilled holes 10 Other (specify)ft.				
	ered shutte		Key punched	2							
SCREEN-F	PERFORATE	ED INTERVALS								to	
	SRAVEL PAG	CK INTERVALS	From	24	π. το ft to 1	20	it., Fr ft Fr	rom	ft	to	ft
	ALIAVEE LA	OK IIVI EIIVAEC	From		ft. to		ft., Fr	rom	ft.	to	ft.
										, , ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	T MATERIA		at cement	2 Cement			ntonite				
Grout Inter	vals: Fron	n1	ft. to2.4	ft., Fro	m	ft.	to	ft., F	rom	ft. to	ft.
What is the nearest source of possible contamination:							10 Livestock pens		14	Abandoned water well	ļ
1 Sep	7	7 Pit privy			11 Fuel storage		Oil well/Gas well				
2 Sewer lines 5 Cess pool					8 Sewage lagoon			12 Fertilizer storage		Other (specify below)	
3 Watertight sewer lines 6 Seepage pit					Feedyard						
Direction fr	om well?	South					How	many feet?	120'		
FROM	ТО		LITHOLOGIC	LOG		FROM	TO		PLUGGING	INTERVALS	
0	2	top soil				105	113	shale	grey		
2	10	clay brown sandy				113	117				
10	31		one yello			117	120		grev		
31	38		one brown						3		
38	51		one M gre						hard free h	"CIVEC	
51	63		one grey	¥					145.	1 6 2004	
63	67	shale k								+ # 200A	
67	70		stone gre	V					SEP	1 6 2004	
70	80	shale		1			<u> </u>				
	81		one grey				<u> </u>		BUREA	U OF WATER	
80											
81		halew c	-								
89	101 limestone grey										
101	102										
102	1.05		one grey								
										under my jurisdiction an	
										knowledge and belief. K	
ì										4-04	•••••
under the b	usiness nan	<sup>ne of</sup> Stra	ader Dril	ling Co	., Inc	· .		by (signature	1 /ms	righten	
INSTRUCT	TIONS: Use type	ewriter or ball point p	en. <i>PLEASE PRESS F</i>	IRMLY and PRINT	clearly. Please	fill in blanks, u	nderline or circl	le the correct ans	were Send top three cop	pies to Kansas Department of H	ealth
and Enviro	nment, Bureau	ot Water, Geology S	ection, 1000 SW Jacks	on St., Suite 420, T	opeka, Kansas	66612-1367.	elephone 785-2	296-5522. Send	OF TO WATER WELL OV	VNER and retain one for your	

records. Fee of \$5.00 for each constructed well.