


1 LOCATION OF WATER WELL: Fraction SE 1/4 SE 1/4 NE 1/4 Section Number 30 Township Number T 10 S Range Number R 22E W
 County: Leavenworth

Distance and direction from nearest town or city street address of well if located within city?
2 1/2 miles west and 1/2 mile north of Basehor

2 WATER WELL OWNER: Ken Cruden
 RR#, St. Address, Box # : 20879 179th Board of Agriculture, Division of Water Resources
 City, State, ZIP Code : Tonganoxie Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL 140 ft. ELEVATION:
 Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL 7.7 ft. below land surface measured on mo/day/yr 9-20-05
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield 5 gpm: Well water was ft. after hours pumping gpm
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 2 PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter 5 in. to ft., Dia in. to ft., Dia 2.82 in. to ft., Dia 2.58 in. to ft.
 Casing height above land surface 24 in., weight lbs./ft. Wall thickness or guage No. .258
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-Cement
 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 90 ft. to 120 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 140 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 25 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? west How many feet? 110

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|------------------------|------|-----|--------------------|
| 0 | 1 | top soil | 114 | 123 | limestone grey |
| 1 | 2 | clay brown | 123 | 126 | shale black limy |
| 2 | 22 | sandstone yellow shaly | 126 | 131 | limestone grey |
| 22 | 29 | shale grey | 131 | 140 | shale grey |
| 29 | 31 | shale brown sandy | | | |
| 31 | 37 | grey sandy | | | |
| 37 | 39 | sandstone brown | | | |
| 39 | 42 | shale grey sandsy | | | |
| 42 | 62 | sandstone brown | | | |
| 62 | 65 | shale grey sandy | | | |
| 65 | 79 | sandstone brown | | | |
| 79 | 84 | sandstone grey brown | | | |
| 84 | 91 | sandstone yellow brown | | | |
| 91 | 114 | sandstone grey | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-27-05 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 182. This Water Well Record was completed on (mo/day/yr) 9-27-05 under the business name of Strader Drilling Co., Inc. by (signature) [Signature]