

10-23-16ab

located on  
 H. O'Connor's  
 map.

VERT

**WATER WELL RECORD**

**DRILLERS LOG OF WELL**

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
0	9	TOPSOIL + CLAY
9	12	SAND, GRAVEL
12	21	CLAY - SANDY
21	23	SAND GRAVEL
23	26	SAND -
26	29	GRAVEL, SAND
29	35	SHALE

Well Owner JOE RADOTINSKY  
 Address WOLCOTT, KANSAS  
 Drilling Contractor W. L. HEUDEE, J  
MUNCIE, KANSAS  
 Date Drilled 3/3/56 to 3/6/56  
 Method of Drilling CABLE  
 Casing: 29'-12" ppc 3' PERF.  
(New, Used—Steel, Galv.—Gage or Weight)  
 Casing Schedule: 8'-9" SLEEVE  
(Amount, Size, Setting)

Screen Data (if any): \_\_\_\_\_


**ON COMPLETED WELL**

Measured depth to water (Static Level) is 11' ft.  
 below LAND SURFACE  
(Land Surface, Top of Casing, Etc.)  
 TESTED YIELD: 20 gallons per MINUTE  
(Min., Hour)  
 as determined by BAILING  
(Bailing, Test Pumping, Etc.)  
 DRAWDOWN: \_\_\_\_\_ ft. after \_\_\_\_\_ hrs.  
 pumping at \_\_\_\_\_ gal. per minute.

REMARKS:

AAB?

**LOCATION OF WELL**  
 [Show location in Section Plat] Elev. 910  
810 ±  
 NW  $\frac{1}{4}$  NE  $\frac{1}{4}$  Sec. 16  
 T. 10 S., R. 23 E. W.  
 County WYANDOTTE



"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."