White—Driller's Copy
Blue—Kansas Geological Survey, University of Kansas, Lawrence
Pink—Customer Copy

location not on map Extend map BRT

WATER WELL RECORD

DRILLERS LOG OF WELL

FROM (FT.)	TO (FT.)	KIND OF MATERIAL, COLOR, ETC. (NOTE WATER ZONES, AMOUNT, QUALITY)
		North Well
0	2	TOp Soil
2	27	Clay Yellow
27	28	Lime Broken
28	34	Clay Blue
34	41	Clay Yellow
41	41½	Lime
41½	66	Clay Yellow
66	80	Broken Lime and Shale
80	81	Lime T.D.

Well Owner Dubs Dread Goff Club
Harold McSpaden
Address 1712 North 70th St. K.C.K.

Drilling Contractor Breuer Drilling Co.
Basehor, Kansas

Date Drilled April 12, 1963

Method of Drilling Rotary
(Cable tool, rotary, reverse rotary, etc.)

Casing Schedule 81' 6¼ steel
(Amount, Size, Setting—New, Used—Steel, Galv.—Gage or Weight)

Screen Data (if any): 12' 6¼" NO. 40 Slot
(Length, Diameter, Slot Size, Setting)
75 to 67 40 to 44

Measured depth to water on completed well (Static Level) is
59 ft. below land
(Land Surface, Top of Casing, Etc.)

TESTED YIELD: 42 gallons per min.
(Min., Hour)
as determined by Testi Pumping
(Bailing, Test Pumping, Etc.)

DRAWDOWN: 14 ft. after 10 hrs.
pumping at 42 gal. per minute.

REMARKS:
North Well
13 Grains hard
1.0 PPM Iron
7.0 ph ok
BR 8/6

LOCATION OF WELL [Show location in Section Plat]
Topographic Sheet Wyeott
Elev. 912 +

NW ¼ NE ¼ Sec. 20
T. 10 S., R. 23 E.
County Wyandotte

"To preserve water well information and to promote the conservation, protection, and development of ground-water resources."

27-1467-S—27-32 10-57-5M SETS