

FINA 9477 Wyandotte Co.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

M.W.# 07

1 LOCATION OF WATER WELL: County: ~~LEAVENWORTH~~ SW 1/4 SE 1/4 SW 1/4 Section Number 36 Township Number T 10 S Range Number R 24 EW  
 Distance and direction from nearest town or city street address of well if located within city? 4812 PARALLEL PARKWAY KANSAS CITY, KS.

2 WATER WELL OWNER: FINA Oil & Chemical  
 RR#, St. Address, Box #: P.O. BOX 2126  
 City, State, ZIP Code: DALLAS, TEXAS 75211  
 Board of Agriculture, Division of Water Resources  
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 2x2 grid with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant.]

4 DEPTH OF COMPLETED WELL: 12' ft. ELEVATION:  
 Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr  
 Pump test data: Well water was ft. after hours pumping gpm  
 Est. Yield gpm. Well water was ft. after hours pumping gpm  
 Bore Hole Diameter 7 1/4 in. to 12 ft. and in to ft.  
 WELL WATER TO BE USED AS:  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only  Monitoring well  
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted  
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded  
 Blank casing diameter 2 in. to 5 ft. Dia in. to ft. Dia in. to ft.  
 Casing height above land surface 0 in. weight SCHED 40 lbs. ft. Wall thickness or gauge No.  
 TYPE OF SCREEN OR PERFORATION MATERIAL:  
 PVC 10 Asbestos-cement  
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)  
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
 SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 0.10 6 Wire wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
 SCREEN-PERFORATED INTERVALS: From 12 ft. to 5 ft. From ft. to ft.  
 GRAVEL PACK INTERVALS: From 12 ft. to 3.5 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 1.5 ft. to 6" ft. From 3.5 ft. to 1.5 ft. From ft. to ft.  
 What is the nearest source of possible contamination:  
 Watertight sewer lines 6 Seepage pit 9 Feedyard 10 Livestock pens 14 Abandoned water well  
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well Gas well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)  
 Direction from well? West How many feet? 40'

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2'	DK BROWN Fine Sandy CLAY			
2'	6.5'	DK OLIVE GRAY SILTY CLAY			
6.5'	11.5'	DK GREENISH GRAY			
11.5'	12'	LIMESTONE,			
Flush Heart					

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed,  reconstructed, or  plugged under my jurisdiction and was completed on (mo/day/yr) 1-11-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 2-12-97 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)