

FINA 9477 Wyandotte Co.

M.W.#9

1 LOCATION OF WATER WELL: County LEAVENWORTH Fraction SW 1/4 SE 1/4 SW 1/4 Section Number 36 Township Number T 10 Range Number R 24  
Distance and direction from nearest town or city street address of well if located within city? 4812 PARALLEL PARKWAY KANSAS CITY, KS.

2 WATER WELL OWNER: FINA OIL & CHEMICAL RR#, St. Address, Box # P.O. BOX 2126 City, State, ZIP Code DALLAS, TEXAS 75211 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 36-acre section with an 'X' in the SW-SE corner] DEPTH OF COMPLETED WELL 14.5' ft. ELEVATION  
Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.  
WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day yr  
Pump test data: Well water was ft. after hours pumping gpm  
Est. Yield gpm Well water was ft. after hours pumping gpm  
Bore Hole Diameter 7 1/4 in. to 14.5 ft. and in. to ft.  
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only Monitoring well  
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day yr sample was submitted

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded  
Blank casing diameter 2 in. to 5 ft. Dia in. to ft. Dia in. to ft.  
Casing height above land surface 0 in. weight SCHED 40 lbs. ft. Wall thickness or gauge No.  
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)  
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
1 Continuous slot Mill slot 6 Wire wrapped 9 Drilled holes  
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)  
SCREEN-PERFORATED INTERVALS: From 14.5 ft. to 5 ft. From ft. to ft.  
GRAVEL PACK INTERVALS: From 14.5 ft. to 3.5 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
Grout Intervals: From 1.5 ft. to 6" ft. From 3.5 ft. to 1.5 ft. From ft. to ft.  
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
Direction from well? East How many feet? 60

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	12'	BROWN with dk brown mottling silty clay, moist			
12'	14.5'	DK OLIVE GRAY, silty clay, saturated			
		Flush Mount			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-8-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 12-12-97 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)