\*> .

USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## Also: Plugging Report

WATER WELL RECORD KSA 82a-1201-1215 Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Konsas 66620

	County	Fraction		Section	number	Township number	Range number	
1. Location of well:	WYANDOTTE	SW 1/4NE 1/4NE	1/4	23	3	110 South	S RZY EASTEN	
2. Distance and dire	ection from nearest town or city:		3. Own	er of wel	1: 3H0	was Bros zwe		
Street address of well location if in city:					street: 1814 EVAST 1945 ST			
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 30 in. Completion date			
N Sketch map:						Well depth 12 ft. 9-4-78		
						7 Cable tool Rotary Driven Dug		
NW	NEN-						ed <u>K</u> Bored Reverse rotary	
E E E						8. Use: Domestic Public supply Industry Irrigation Air conditioning Stock Lawn Oil field water X Other 9. Casing: Material Height: Above or below		
							Height: Above or below in.	
S	5					RMP PVC	lbs./ft.	
1 <del>4 1</del> M		TANAN TA		From	То	Dia. 10 in. to 57 ft. d	lepth Wall Thickness: Inches or lepth gage No. 1250	
5. Type ond color of	mareriai			rrom	10	10. Screen: Manufacturer		
Top Sol				0	4	TypeGEAUEL GUY	Hapia 18"	
01				4		Slot/gauze • • • • •	Length <del>1 t</del> 0	
Crm				<del>  '</del>		Set between 37	ft. andft.	
Fruz S.	ANDY S.LA			7	13	Gravel pack?K_ Size	range of material 3/8 6/2	
chang				13	14	11. Static water level:ft. below land	mo./day/yr.	
Fine V	MED SAWD			14	40	12. Pumping level below le		
Sicty Fuz Spans				40	49		hrs. pumping g.p.m.	
MED SAND				49	62	Estimated maximum yield		
	ς .			1.		Yes <b>Y</b> No		
hour ?	Dana (			62	12	14. Well head completion: Pitless adapter	18 Inches above grade	
						15. Well grouted? _Ws		
WELL CASING AND SERRU RAMOUED						With: Neat cement ft.	Bentonite Concrete	
	sweek till phis			***	$\lfloor -  ceil$	16. Nearest source of possi	ible contamination:	
T- 12'	BELOW EXIST			rec.	-4,	ft Direction _ Well disinfected upon com	Туре	
, ,		, , , , ,	,			17. Pump:	_ <b>∕</b> Not installed	
brid b,	hucers From	15' to 4 Be	ملصاح	}		Manufacturer's name Model number	HP Volts	
Gasons, Somo phaces From 4' to						Length of drop pipe	ft. capacityg.p.m.	
Green	ne Common					Type: Submersible	Turbine	
<u> </u>	- Samana					Jet	Reciprocating	
10 Elauata	10 Parades	I sheet if needed)		<u> </u>		Centrifugal 20. Water well contractor	Other	
18. Elevation:	Completed	10-23-78				This well was drilled under	my jurisdiction and this report	
Topography:	`					is true to the best of my kn	nowledge and belief. Annuarium Carib	
Hill						Rusiness name	License No.	
Slope						Address Downsus	7 2/21/79	
Upland _x^Valley						Signed Authorized I	representative Date	