

1 LOCATION OF WATER WELL: County: WYANDOTTE	Fraction: SW 1/4 SW 1/4 SW 1/4	Section Number: 27	Township Number: T 10 S	Range Number: R 25 E/W
---	---------------------------------------	---------------------------	--------------------------------	-------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3126 BRINKERHOFF, KANSAS CITY KS

2 WATER WELL OWNER: UNISON	PF-6
RR#, St. Address, Box #: 3126 BRINKERHOFF	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: KANSAS CITY, KS	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 51.90 ft. ELEVATION:
--	--

1 Mile

Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter: **11** in. to **11** in. and **4.25** in. to **55** in.

WELL WATER TO BE USED AS:

5 Public water supply	8 Air conditioning	11 Injection well
1 Domestic	3 Feedlot	6 Oil field water supply
2 Irrigation	4 Industrial	7 Lawn and garden only
		10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No ☒ If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No ☒

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
☒ Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 10 in. to 10.5 in. Dia 4 in. to 11.6 in. Dia			Threaded ☒
Casing height above land surface: 3 in. weight lbs./ft. Wall thickness or gauge No.			
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	☒ Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	☒ Wire wrapped 0.010"	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 11.6 ft. to 51.9 ft.		
	From ft. to ft.		
GRAVEL PACK INTERVALS:	From 11.2 ft. to 11.4 ft.		
	From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	☒ Cement grout	☒ Bentonite	4 Other
Grout Intervals:	From 0 ft. to 10.5 ft.	From 10.5 ft. to 11.2 ft.	From ft. to ft.	
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
				14 Abandoned water well
				15 Oil well/Gas well
				☒ Other (specify below)
				INDUSTRIAL SITE

Direction from well?		LITHOLOGIC LOG		PLUGGING INTERVALS	
FROM	TO		FROM	TO	
0	4.0	LT BRN CLAY			
4.0	10.0	BRN CLAY			
10.0	18.0	LT BRN CLAY - SILT			
18.0	24.0	BRN CLAY - SILT - F. SAND			
24.0	25.0	DK BRN CLAY - SILT			
25.0	55.0	GRAY SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-5-96 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 1-5-97 under the business name of TERRACON CONSULTANTS IN by (signature) Clay P. Dwyer
--