

1 LOCATION OF WATER WELL: County: WYANDOTTE	Fraction SW 1/4 SW 1/4 SW 1/4	Section Number 27	Township Number T 10 S	Range Number R 25 EW
---	---	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

3126 BRINKERHOFF KANSAS CITY KS

2 WATER WELL OWNER: UNISON	MW-6
RR#, St. Address, Box #: 3126 BRINKERHOFF	Board of Agriculture, Division of Water Resources
City, State, ZIP Code: KANSAS CITY KS 66115	Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 38.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 19.0 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 19.0 ft. below land surface measured on mo/day/yr 3-22-97
	Pump test data: Well water was ft. after hours pumping gpm
	Est. Yield gpm: Well water was ft. after hours pumping gpm
	Bore Hole Diameter 8.25 in. to 39.0 ft. and in. to ft.
WELL WATER TO BE USED AS:	
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted	
Water Well Disinfected? Yes No <input checked="" type="checkbox"/>	

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 33.0 ft. Dia			Threaded <input checked="" type="checkbox"/>
Casing height above land surface in. weight lbs./ft. Wall thickness or gauge No SCHED 40			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot 0.010"	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:	From 33.0 ft. to 38.5 ft.	7 Torch cut	10 Other (specify)
GRAVEL PACK INTERVALS:	From 27.0 ft. to 38.5 ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other CONCRETE
Grout Intervals:	From 0.0 ft. to 0.6 ft.	From 0.6 ft. to 12.6 ft.	From 12.6 ft. to 27.0 ft.	
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
INDUSTRIAL SITE				
Direction from well? How many feet?				

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	5.0	BROWN CLAY (FILL)			
5.0	7.0	DK GRAY SILT			
7.0	9.0	GRAY CLAYEY SILT			
9.0	12.0	GRAY SILTY CLAY			
12.0	19.0	GRAY CLAYEY SILT			
19.0	39.0	BROWN - GRAY FINE SAND			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-22-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 3-23-97 under the business name of TERRACON CONSULTANTS INC by (signature) Clay P. Nye
--