



WATER WELL RECORD Form WWC 5 KSA 82a 12'12


1 LOCATION OF WATER WELL: County WYANDOTTE, Fraction SE 1/4, Section Number 27, Township Number 10S, Range Number R25

Distance and direction from nearest town or city street address of well if located within city? 200 FUNDON ROAD KANSAS CITY, KANSAS

2 WATER WELL OWNER: B. BRUCE COMPANY, 1300 WILLOW LAKE BLVD, ST. PAUL, MINNESOTA 55110

Board of Agriculture Division of Water Resources, Application Number 74246

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: DEPTH OF COMPLETED WELL 20, ELEVATION 742.46



WELL'S STATIC WATER LEVEL NM, 15 ft below land surface measured on the day of... Pump test data: Well water was... hours pumping... gpm... Well water was... hours pumping... gpm... Bore Hole Diameter... ft... and... ft... WELL WATER TO BE USED AS: 1 Domestic, 2 Irrigation, 3 Feedlot, 4 Industrial, 5 Public water supply, 6 Other field water supply, 7 Lawn and garden only, 8 Air conditioning, 9 Other (specify), 10 Other (specify below), 11 Injection well

4 TYPE OF BLANK CASING USED: 1 Steel, 2 PVC, 3 RMP (SP), 4 ABS, 5 Wrought iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), CASING JOINTS: Glued, Clamped, Wedged, Threaded

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless steel, 4 Galvanized steel, 5 Fiberglass, 6 RMP (SP), 7 Concrete tile, 8 ABS, 9 Other (specify), 10 Asbestos cement, 11 Other (specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered slitter, 3 Mesh, 4 Key punched, 5 Galvanized wrapped, 6 Wire wrapped, 7 Trench cut, 8 Saw cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN PERFORATION INTERVALS: From 20 ft to 10 ft, From 10 ft to 0 ft, From 0 ft to 0 ft, From 0 ft to 0 ft, From 0 ft to 0 ft

5 GROUT MATERIAL: 1 Seal cement, 2 Cement grout, 3 Portland cement, 4 Other, Grout intervals: From 0 ft to 2 ft, From 2 ft to 10 ft, From 10 ft to 10 ft, From 10 ft to 10 ft, From 10 ft to 10 ft

6 LITHOLOGIC LOG: FROM 0 TO 7.5, 7.5 TO 20. LITHOLOGIC LOG: GRAY TO BROWN MOIST SOFT TO STIFF SILTY CLAY, LIGHT BROWN BELOW TO TAN, MOIST TO WET LOOSE, FINE-GRAINED SAND. FROM 0 TO 7.5, 7.5 TO 20. PLUGGING INTERVALS: 39.08 35.08, 94.36 53.63, 39.1431, 94.6149

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on 9/2/1966. Water Well Contractor's License No. 568 MAXS. This Water Well Record was completed on 1/10/1966 by (signature) Daniel H. ...