

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Wyandotte		NE ¼ NW ¼ SE ¼	34	T 10 S	R 25 E/W
Distance and direction from nearest town or city street address of well if located within city? 1220' SE of Fairfax Tr. & Stanley Rd., KC, Kan.					
2 WATER WELL OWNER: MAGELLAN PIPELINE LLC					
RR#, St. Address, Box #		13424 WEST 98 <sup>TH</sup> STREET		Board of Agriculture, Division of Water Resources	
City, State, ZIP Code		SHAWNEE MISSION KS 66215		Application Number:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 65 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. . . . . ft. 2. . . . . ft. 3. . . . . ft.			
		WELL'S STATIC WATER LEVEL: 23.03 ft. below land surface measured on mo/day/yr 10/1/2003			
		Pump test data: Well water was NA ft. after . . . . . hours pumping . . . . . gpm			
		Est. Yield NA gpm: Well water was . . . . . ft. after . . . . . hours pumping . . . . . gpm			
		Bore Hole Diameter 8 in. to 65 ft. and . . . . . in. to . . . . . ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No <input checked="" type="checkbox"/> If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No <input checked="" type="checkbox"/>			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)		5 Wrought iron	
2 PVC		4 ABS		6 Asbestos-Cement	
				7 Fiberglass	
Blank casing diameter 2 in. to 55 ft. Dia				8 Concrete tile	
Casing height above land surface 0 in. weight				9 Other (specify below)	
TYPE OF SCREEN OR PERFORATION MATERIAL				CASING JOINTS: Glued . . . . . Clamped . . . . .	
1 Steel		3 Stainless steel		Welded . . . . .	
2 Brass		4 Galvanized steel		Threaded <input checked="" type="checkbox"/>	
3 Mill slot		5 Fiberglass		7 PVC	
4 Key punched		6 Concrete tile		8 RMP (SR)	
SCREEN OR PERFORATION OPENINGS ARE:				9 ABS	
1 Continuous slot		5 Gauzed wrapped		10 Asbestos-cement	
2 Louvered shutter		6 Wire wrapped		11 Other (specify)	
		7 Torch cut		12 None used (open hole)	
				8 Saw cut	
				9 Drilled holes	
				10 Other (specify)	
SCREEN-PERFORATED INTERVALS:		From 55 ft. to 65 ft.		From . . . . . ft. to . . . . . ft.	
		From . . . . . ft. to . . . . . ft.		From . . . . . ft. to . . . . . ft.	
GRAVEL PACK INTERVALS:		From 52 ft. to 65 ft.		From . . . . . ft. to . . . . . ft.	
		From . . . . . ft. to . . . . . ft.		From . . . . . ft. to . . . . . ft.	
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout		3 Bentonite	
4 Other					
Grout Intervals: From 0 ft. to 3 ft.		From 3 ft. to 47 ft.		From 47 ft. to 52 ft.	
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines		7 Pit privy	
2 Sewer lines		5 Cess pool		8 Sewage lagoon	
3 Watertight sewer lines		6 Seepage pit		9 Feedyard	
				10 Livestock pens	
				11 Fuel storage	
				12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well?				How many feet? 0	
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.4	Asphalt,	24.4	24.8	Sand, silty, very fine grained, wet, Dark Green
0.4	1	Gravel fill,	24.8	30	Silt, sandy, trace clay, nonplastic, Dark Green
1	3	Clay, some sand, medium plasticity, Black	30	40	Sand, clayey, medium to fine grained, wet, Da
3	4	Clay, silty, trace plasticity, Very Dark Gray	40	50	Sand, clayey, medium grained, wet, Dark Gre
4	4.8	Silt, sandy, nonplastic, Greenish Gray	50	65	Sand, clayey, medium to coarse grained, wet,
4.8	6	Sand, silty, very fine grained, Greenish Gray			
6	6.8	Clay, silty, trace plasticity, Dark Greenish Gr			
6.8	7.6	Silt, sandy, nonplastic, Greenish Gray			
7.6	8	Silt, sandy, trace Clay, nonplastic, Greenish G			
8	9	Silt, trace sand, nonplastic, Grayish Brown			
9	14.4	Sand, very fine grained, damp to moist, Light			
14.4	18	Sand, silty, very fine grained, Light Brownish			
18	18.8	Clay, silty, high plasticity, Very Dark Gray			MW-10D, Flushmount
18.8	23.8	Sand, silty, very fine to fine grained, Light Bro			Project Name: BM - Mile Marker #1
23.8	24.4	Sand, fine grained, wet, Light Brownish Gray			GeoCore # 1040, #
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10/1/2003, and this record is true to the best of my knowledge and belief.					
Kansas Water Well Contractor's License No. 527		This Water Well Record was completed on (mo/day/yr) 10/17/2003			
under the business name of GeoCore Inc.		by (signature) Dan R. R.			
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

EW

SEC.

%

%

%