

71728

AS-99

1 LOCATION OF WATER WELL: County: <u>Wyandotte</u>	Fraction <u>SW 1/4 SW 1/4 SW 1/4</u>	Section Number <u>27</u>	Township Number <u>T 10</u>	Range Number <u>R 25</u>
-------------------------------------------------------	-----------------------------------------	-----------------------------	--------------------------------	-----------------------------

Distance and direction from nearest town or city street address of well if located within city?
1/2 Block North of Funston Rd. & Brinkerhoff Rd. Kansas City, KS 66115

2 WATER WELL OWNER: Dow Chemical Corp.
 RR#, St. Address, Box #: P.O. Box 9361 - 3200 Kanawha Turnpike
 City, State, ZIP Code: South Charleston, WV 25303
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 46.0 ft. ELEVATION: ft.
 Depth(s) Groundwater Encountered 1. 23.0 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 24.24 ft. below land surface measured on mo/day/yr 11-12-04
 Pump test data: Well water was ft. after hours pumping gpm
 Est. Yield gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter. 3.25 in. to ft., and in. to ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Air Sparger
 Was a chemical/bacteriological sample submitted to Department? Yes. N X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes N X

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped.
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 Blank casing diameter 1 in. to 45 ft., Dia in. to ft., Dia in. to ft.
 Casing height above land surface. 24 in., weight lbs./ft. Wall thickness or gauge No. Set. 40
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify) ft.
 SCREEN-PERFORATED INTERVALS: From 45 ft. to 46 ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 46 ft. to 44 ft., From 44 ft. to 42 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 8 ft. to Surface ft., From 42 ft. to 8 ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
old Air Sparger Paines
 Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Lean Clay, brown, Hard, Dry			
5	10	Lean Clay, DK Brown, Moist, Silty			
10	20	Mud, Lean Clay w/ Trace Sand			
20	25	Mud, med brained Sand, Gray			
25	30	Med to Fine Sand, DK Gray, Wet			
30	40	DK Gray, Wet, Fine brained Sand			
40	46	" "			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-3-04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 606 This Water Well Record was completed on (mo/day/yr) 11-15-04 under the business name of PSA Environmental by (signature) [Signature]