CORRECTION(S) TO WATER WELL RECORD (WWC-5) (to rectify lacking or incorrect information) County: Wyandotte changed to: Location changed to: Section-Township-Range: 27 - 405 - 25EFraction (1/4 1/4 1/4): ______ **SW SW** Other changes: Initial statements:

Changed to:							
Comments:							
verification method:	well	addres	s, city	map,	and		
North			•	•			
		/	,	/	initials: DD /	date: 3/7/200	• ~

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

Location listed as:

	R WELL RECORD F	orm WWC-5	KSA 82a-12	12 ID No	SV-89	<u> </u>	
1 LOCATION OF WATER WELL:	Fraction			n Number	Township Nun		Number
County: WYANDOTTE	14 SW	$\frac{\sqrt{4}}{\sqrt{5}}$.7	T 40	s RZ	5 (Pw
Distance and direction from nearest town		vell if located wit	hin city?				
3126 BRINKERHOR	FRD K	c KS	66	115			
2 WATER WELL OWNER: JCTOM	e E. Cibrik	3200	3300	Kanowh	a Tumpil	زف	
RR#, St. Address, Box # :	Carbide Corp.	Awas	Charlest	20803	7	culture, Division of Wat	ter Resources
	DEPTH OF COMPLETE	D WELL			l:		
AN "X" IN SECTION BOX:	epth(s) Groundwater End	countered _ 1		ft. 2	•••••	ft. 3	ft.
<u>N</u> W	/ELL'S STATIC WATER L	.EVEL ሩ.ಎ <i>६</i> .	Qft. below	land surface me	easured on mo/d	ay/yr	
						hours pumping	
	st. Yield gpm /ELL WATER TO BE US		as olic water sup		ir conditioning		gpm
"	1 Domestic 3 Fee		field water su		Dewatering	Other (Specify	below)
W	2 Irrigation 4 Indu	ıstrial 7 Dor	mestic (lawn	& garden) 10 M	Monitoring well	416 SDar	من ا
					VAPO	N EXTRACT	40N
SW SE W	as a chemical/bacteriolo	gical sample sub	mitted to De	partment? Yes .	No;	If yes, mo/day/yrs san	nple was sub-
	itted				Well Disinfected		No
S							
5 TYPE OF BLANK CASING USED:	5 Wrough	nt iron	8 Concrete	tile	CASING JOIN	TS: Glued Clar	nped
1 Steel 3 RMP (SR)		os-Cement		ecify below)		Welded	
PVC 4 ABS	7 Fiberal					Threaded	,
Blank casing diameter	,in. to	ft., Dia		in. to	ft., Dia	jp_to	,ft.
Casing height above land surface	7 in., we	ight		lbs./	ft. Wall thickness	s or guage No.	• 70
TYPE OF SCREEN OR PERFORATION			7)PVC	(2-)		stos-Cement	
1 Steel 3 Stainless S 2 Brass 4 Galvanized	3		9 ABS	(SR)		(Specify)used (open hole)	
2 5,000							
SCREEN OR PERFORATION OPENING:		5 Guazed 6 Wire wra			Saw cut Drilled holes	11 None (or	en hole)
1 Continuous slot 2 Louvered shutter 4 Key	slot punched	7 Torch cu	• •				ft
	From				(, , , ,		
SCREEN-PERFORATED INTERVALS:	From	π. το	<i>j. W</i>	ft., From ft From		ft. to	tt.
GRAVEL PACK INTERVALS:	From	ft. to	14	ft., From		ft. to	ft.
90/10	From	ft. to	<i>j.</i> -j	ft., From		ft. to	ft.
C CROUT MATERIAL A North			0.0	4 01			
6 GROUT MATERIAL: 1 Neat co	ft. to ft.,	ent grout	3 Benton				
What is the nearest source of possible co		From					
•		7 Dit priva		10 Livestock		14 Abandoned wa	
1 Septic tank 4 Lateral 2 Sewer lines 5 Cess po		7 Pit privy		11 Fuel storage		15 Oil well/Gas well 16 Other (specify below)	
		8 Sewage lagoon 9 Feedyard		12 Fertilizer storage13 Insecticide storage		Former Source IN	
3 Watertight sewer lines 6 Seepag Direction from well?	e pit	9 Feedyalu		How many fee	• •	LAG	
FROM TO	LITHOLOGIC LOG		FROM	TO TO		GING INTERVALS	
			PHOW	10	PLUG	GING INTERVALS	
	silts + clays	1				 	
	Sonds, fine	7					
medium							
							-
7 CONTRACTOR'S OR LANDOWN TO	OCCUTICATION: TO		20	nd (0)			
CONTRACTOR'S OR LANDOWNER'S completed on (mo/day/year)	4 TOWN: This	water well was	X · 1			gged under my jurisdic Lof my knowledge apd	
Water Well Contractor's Licence No	704	This Water We			4	or my knowledge and	Dellei. Nalisas
under the business name of	144	446	100010 Wa	by (signa		il Mari	
INSTRUCTIONS: Use typewriter or ball point pen.	PLEASE PRESS FIRMLY and PR	INT clearly Please fill	in blanks underlie		— <i>FJ W</i>	Title Applies to Kapeae Banari	tment of Health
and Environment, Bureau of Water, Geology Section							
records. Fee of \$5.00 for each constructed well.							