

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

County: Wyandotte

Location listed as:

Location changed to:

Section-Township-Range: 34-105-33W

34-105-25E

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): NW SE SE

NW SE SE

Other changes: Initial statements: _____

Changed to: _____

Comments: _____

verification method: Written & legal descriptions, city map, position on plat map, and North Kansas City 1:24,000 topo. map.

initials: DRH date: 5/20/2005


submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Wyandotte	NW 1/4 SE 1/4 SE 1/4	34	T 10 S	R 33 X/W

Distance and direction from nearest town or city street address of well if located within city?
 Donovan & Industrial Blvd.; Kansas City, Kansas

2 WATER WELL OWNER: Phillips Petroleum
 RR#, St. Address, Box #: P.O. Box 15036 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: Kansas City, Kansas 66115 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 58.2 ft. ELEVATION: 741
 Depth(s) Groundwater Encountered 1. 11 ft. 2. ft. 3. ft.
 WELL'S STATIC WATER LEVEL 11.3 ft. below land surface measured on mo/day/yr 9/7/84
 Pump test data: Well water was 34.8 ft. after 2 hours pumping 803 gpm
 Est. Yield 400 gpm: Well water was ft. after hours pumping gpm
 Bore Hole Diameter .20 in. to 58.2 ft., and in. to ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was sub-
 mitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X
 7 Fiberglass Threaded
 Blank casing diameter 20 in. to 38.2 ft., Dia. in. to ft., Dia. in. to ft.
 Casing height above land surface 38 in., weight 78.60 lbs./ft. Wall thickness or gauge No. 375
 TYPE OF SCREEN OR PERFORATION MATERIAL:
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)
 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes
 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 38.2 ft. to 58.2 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.
 GRAVEL PACK INTERVALS: From 14 ft. to 58.2 ft., From ft. to ft.
 From ft. to ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.
 What is the nearest source of possible contamination:
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage
 Direction from well? all around How many feet? 25

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0.0	5.0	Gravel, clay (fill)	36.5	40.0	Same
5.0	10.0	Gray sandy silt, very soft	40.0	41.5	Gray med. to fine sand, trace coars
10.0	15.0	Same	41.5	45.0	Gray fine to med. sand, trace v. fi
15.0	16.5	Same	45.0	46.5	Same
16.5	19.0	Same	46.5	50.0	Same
19.0	20.0	Gray very fine to fine sand	50.0	51.5	Gray fine to very fine sand
20.0	21.5	Same	51.5	52.5	Same
21.5	25.0	Same	52.5	55.0	Limestone boulders, coarse sand
25.0	26.5	Same	55.0	59.0	Same
26.5	29.0	Same	59.0	59.5	Limestone, hard
29.0	30.0	Gray fine to very fine sand	59.5	Total	Depth
30.0	31.5	Same			
31.5	33.0	Same			
33.0	35.0	Gray med. sand, trace v. fine sand			
35.0	36.5	Gray med. sand, trace coarse sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/7/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 1/15/84 under the business name of Layne-Western Company, Inc. by (signature) D.D. Smith

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T 10
R 33
EW
SEC. 34
NW 1/4
SE 1/4
SE 1/4