

**CORRECTION(S) TO WATER WELL RECORD (WWC-5)**  
(to rectify lacking or incorrect information)

County: Wyandotte

Location listed as:

Location changed to:

Section-Township-Range: 34-10-33

34-10S-25E

Fraction ( ¼ ¼ ¼): SW SE SE

SW SE SE

Other changes: Initial statements: \_\_\_\_\_

Changed to: \_\_\_\_\_

Comments: \_\_\_\_\_

verification method: written & legal descriptions, city map, position on plat map, and North Kansas City 1:24,000 topo. map.

initials: DRL date: 5/20/2005


submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726  
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

1 LOCATION OF WATER WELL: County: Wyandotte	Fraction SW 1/4 SE 1/4 SE 1/4	Section Number 34	Township Number T 10 S	Range Number R 33 E/W
--	----------------------------------	----------------------	---------------------------	--------------------------

Distance and direction from nearest town or city street address of well if located within city?  
 Donovan & Industrial Blvd.; Kansas City, Kansas

2 WATER WELL OWNER: Phillips Petroleum  
 RR#, St. Address, Box #: P.O. Box 15036 Board of Agriculture, Division of Water Resources  
 City, State, ZIP Code: Kansas City, Kansas 66115 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL: 56.4 ft. ELEVATION: 740  
 Depth(s) Groundwater Encountered 1. 14 ft. 2. ft. 3. ft.  
 WELL'S STATIC WATER LEVEL: 13.7 ft. below land surface measured on mo/day/yr 8-22-84  
 Pump test data: Well water was 23.1 ft. after 2 hours pumping 506 gpm  
 Est. Yield 200 gpm; Well water was ft. after hours pumping gpm  
 Bore Hole Diameter: 36 in. to 56.4 ft., and in. to ft.  
 WELL WATER TO BE USED AS:  
 5 Public water supply 8 Air conditioning 11 Injection well  
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well  
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:  
 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded X  
 7 Fiberglass Threaded

Blank casing diameter: 20 in. to 36.4 ft. Dia in. to ft. Dia in. to ft.  
 Casing height above land surface: 42 in., weight 78.60 lbs./ft. Wall thickness or gauge No. 375

TYPE OF SCREEN OR PERFORATION MATERIAL:  
 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement  
 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)  
 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:  
 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes  
 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 36.4 ft. to 56.4 ft., From ft. to ft.  
 GRAVEL PACK INTERVALS: From 14 ft. to 56.4 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other  
 Grout Intervals: From 0 ft. to 14 ft., From ft. to ft., From ft. to ft.

What is the nearest source of possible contamination:  
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage  
 Direction from well? all around How many feet? 50

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0.0	5.0	Gray clay (fill)	35.0	36.5	Same
5.0	8.0	Gray silty clay	36.5	40.0	Gray fine to very fine sand
8.0	12.0	Gray clay silt, very soft	40.0	41.5	<del>XXXX</del> Gray fine to medium sand
12.0	15.0	Gray silty clay	41.5	43.0	Same
15.0	16.5	Gray sandy silt, trace clay	43.0	44.0	Gray fine to med. sand, trace fine
16.5	17.0	Same	44.0	45.0	Gray fine to medium sand
17.0	20.0	Gray very fine sand	45.0	46.5	Same
20.0	21.5	Same	46.5	50.0	Same
21.5	22.0	Same	50.0	51.5	Same
22.0	25.0	Gray fine to med. sand, some fine	51.5	52.0	Limestone boulders & clay, trace gray
25.0	26.5	Gray fine to med. sand, some fine	52.0	56.5	Limestone boulders & clay
26.5	27.0	Same	56.5	57.0	Gray limestone, clay
27.0	30.0	Gray fine to very fine sand	57.0	Total	Depth
30.0	31.5	Same			
31.5	35.0	Same			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/15/84 8/22/84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 102 This Water Well Record was completed on (mo/day/yr) 11/15/84 under the business name of Layne-Western Company, Inc. by (signature) [Signature]

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY  
T 10  
R 33  
EW  
SEC. 34  
SW  
SE 1/4  
SE 1/4