CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:	County: Wyandotte Location changed to:			
Section-Township-Range: 22-50N-33W	35-105-25E			
Fraction (1/4 1/4 1/4): NW NW SE	35-105-25E C N2 SW			
Other changes: Initial statements:				
Changed to:				
Comments:				
verification method: Map of well location: North Kansas City 1:24,000	s from owner, and			
North Kansas City 1:24,00	o topo, map.			
,	initials: ORL date: 9/9/2005			

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726 to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212 LOCATION OF WATER WELL: Section Number Township Number Range Number County: Wyandotte T 750N s EW Distance and direction from nearest town or city street address of well if located within city? 2 WATER WELL OWNER: CONOCO Phillips Company
RR#, St. Address, Box # : 1218 Phillips Bldg 4205 Keeler Ave Board of Agriculture, Division of Water Resources AN "X" IN SECTION BOX: WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr Pump test data: Well water wasft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm - NW -- NE -8 Air conditioning WELL WATER TO BE USED AS: 5 Public water supply 11 Injection well 1 Domestic 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 3 Feedlot 7 Domestic (lawn & garden) Monitoring well 2 Irrigation 4 Industrial Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yrs sample was sub-Water Well Disinfected? Yes TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped Welded 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) **PVC** 4 ABS 7 Fiberglass Threaded in, to ft., Dia in. to ft., Dia in. to ft. Blank casing diameter2 TYPE OF SCREEN OR PERFORATION MATERIAL: 10 Asbestos-Cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 Other (Specify) 4 Galvanized Steel 6 Concrete tile 9 ABS 2 Brass 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Guazed wrapped 8 Saw cut 11 None (open hole) Mill slot 6 Wire wrapped 9 Drilled holes 1 Continuous slot 7 Torch cut 10 Other (specify)ft. 2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From GRAVEL PACK INTERVALS: 4 Other 2 Chip II Cemen 3 Bentonite **GROUT MATERIAL:** 2 Cement grout 1 Neat cement What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well Fuel storage 1 Septic tank 4 Lateral lines 7 Pit privy 15 Oil well/Gas well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below) 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage Direction from well? How many feet? FROM LITHOLOGIC LOG **FROM** PLUGGING INTERVALS Brr Sity Sard CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No This Water Well Record was completed on (mo/day/yr) under the business name of by (signature)

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well



 PROJECT NUMBER
 BORING NUMBER

 321564.SI.01
 PZ-402
 SHEET 1 OF 1

SOIL BORING LOG

PROJECT : Conoco Phillips - Supplemen	CT: Conoco Phillips - Supplemental SI NORTHING: 309636.83 EASTING: 2276855.72		2276855.72
ELEVATION: 747.99 ft b.t.o.c.	DRILLING CONTRACTOR : Max's Enterprises Inc.		
DRILLING METHOD AND EQUIPMENT			
WATER LEVELS : 20.0' bgs		START: 10/29/04 0955	END: 10/29/04 1025
DEPTH BELOW SURFACE (FT)	STANDARD	SOIL DESCRIPTION	COMMENTS
RECOVERY (FT) #/TYPE	PENETRATION TEST RESULTS	SOIL NAME, USCS GROUP SYMBOL, COLOR, MOISTURE CONTENT, RELATIVE DENSITY,	DEPTH OF CASING, DRILLING RATE, DRILLING FLUID LOSS,
1 1 1 5	6"-6"-6"	OR CONSISTENCY, SOIL STRUCTURE,	TESTS, AND INSTRUMENTATION.
	(N)	MINERALOGY. 0.0': Well graded sand and gravel (GW-	Notes
No Soil Sampling		brown, moist, fill	
-		3.0': Brown, grain size decreasing, fill,poorly sorted	- -
5		4.0': Silty sand (SM), brown, moist, occasional coarse sand, fine gravel, clay	_
-		6.0': Silty sand with trace gravel (SM),	-
-		-	-
-		-	-
10		10.0': Silty sand (SM), reddish brown, mois to coarse, poorly sorted with subrounded fine gravel, organic material (roots)	 -
 		12.0': Grayish brown _	-
- .		13.0': More gray, slight odor, organic material –	_
15		15.0': Silty sand (SM), fine to medium, no no organic material	_
		17.0': Silty clay (CL), brownish gray, moist, plastic, slight odor	_
		_	-
20		20.0': Silty sand (SM), brownish gray, fine to medium, no organic material	
-		22.0': Increased moisture	-
- -			- -
25			_
-		26.0': Silty sand (SM), dark gray, wet to sa fine, HC slight odor	-
-		32.0': Silty sand (SM), dark gray, saturated,	-
_ 35_		poorly sorted, fine to coarse, slight HC odol 35.0': End of boring	-
_			

